

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 867 877 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
30.09.1998 Bulletin 1998/40

(51) Int Cl.⁶: **G11B 20/12, G11B 27/28,
G11B 20/10**

(21) Application number: **98302261.7**

(22) Date of filing: **25.03.1998**

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: **Samsung Electronics Co., Ltd.**
Suwon-city, Kyungki-do (KR)


(72) Inventor: **Heo, Jung-Kwon**
Songpa-gu, Seoul (KR)

(30) Priority: **25.03.1997 KR 9710330**
09.10.1997 KR 9751861

(74) Representative: **Chugg, David John**
Appleyard Lees,
15 Clare Road
Halifax, West Yorkshire HX1 2HY (GB)

(54) DVD-audio disk, and apparatus and method for playing the same

(57) A DVD-Audio which includes a data zone for storing data to be reproduced and an information zone for storing information on the data to be reproduced. The information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS). The AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles. The data zone includes the audio titles each having an audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs). The ATSI includes a plurality of audio stream attributes each having an audio coding mode, first to third quantization bit numbers, first to third sampling frequencies and decoding algorithm information relating to the number of audio channels. Each of the AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute.

**FIG. 1****EP 0 867 877 A2**

Description

The present invention relates to a digital versatile disk (DVD), and an apparatus and method for playing the DVD, and more particularly, to an audio DVD (hereinafter referred to as "DVD-Audio") and an apparatus and method for playing the same.

Recently, there has been developed a so-called video DVD (hereinafter referred to as "DVD-Video"), which has a considerably higher storage capacity than a laser disk (LD) so as to realize a significantly improved picture and sound quality. If the DVD is employed to store and retrieve only audio data, such DVD is called a DVD-Audio. The DVD-Audio provides means for storing and retrieving a large amount of audio data having a significantly improved quality compared to a compact disk (CD) or a digital audio tape (DAT).

The conventional CD stores an audio signal as linear pulse code modulated (PCM) audio data quantized into 16 bits by employing a sampling frequency of 44.1KHz. The digital data stored in the CD is converted into analog signals by means of a CD player. The CD is much more convenient to use as compared to the previous microgroove phonograph record (LP), but is regarded as having a lower sound quality than the analog LP. This is because the audio signals are sampled at 44.1KHz and quantized into 16 bits to be stored into a CD. Moreover, the audible frequency range may be over 20KHz, and the dynamic range must be over 120dB. In addition, the CD can only store audio signals of at most two channels, and therefore is impossible to store and reproduce the audio data concerned with multi-channel music. In these circumstances, there have been proposed various methods to improve the sound quality of the CD by increasing the numbers of the sampling frequency and the audio channels.

The DVD provides means to record video and audio data at high density. In this case, the video data is recorded in the MPEG (Moving Picture Expert Group) while the audio data is recorded in the linear PCM format, dolby AC-3 format, MPEG format, etc. Hence, the DVD-Video player is designed to reproduce both video and audio data recorded in a DVD-Video. Such a DVD-Video prepared to necessarily store video data is very uneconomical in view of the storage space when used for storing audio data only.

The audio data recorded in a DVD-Video has a much higher quality than that in a CD since the audio data of the DVD has a higher sampling frequency and larger numbers of quantization bits and channels than that of the CD. Namely, the DVD player reproduces high quality audio data in multiple channels.

The DVD is possible to transfer data at 10.08Mbps at most. This makes it possible to reproduce data sampled at 192KHz in two channels. This also approaches the maximum sampling frequency proposed as a prerequisite for the next advanced audio system at the Advanced Digital Audio Conference held in Japan in April, 1996. Thus, if audio data are recorded in a DVD-Audio, the DVD player may reproduce sounds of a significantly improved quality over that reproduced from the DVD-Video.

It is an object of the present invention to provide a DVD-Audio for storing digital audio signals sampled at the maximum sampling frequency and quantized in the maximum number of bits with the number of channels limited by the data transfer speed in linear PCM.

It is another object of the present invention to provide a DVD-Audio for compressively coding digital audio signals sampled at the maximum sampling frequency and quantized in the maximum number of bits and storing them with the number of channels limited by the data transfer speed and the coding system in linear PCM.

It is still another object of the present invention to provide a DVD player for playing a DVD-Audio recorded in linear PCM and a method therefor.

It is a further object of the present invention to provide a DVD player for playing a DVD-Audio recorded with audio data compressively coded and a method therefor.

It is further another object of the present invention to provide a DVD player for properly playing a DVD-Video or DVD-Audio by distinguishing them.

According to a first aspect of the present invention, a DVD-Audio includes a data zone for storing data to be reproduced and an information zone for storing information on the data, the information zone including directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein the AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein the data zone includes the audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), the ATSI includes a plurality of audio stream attributes each having an audio coding mode indicator, first to third quantization bit numbers, first to third sampling frequencies and decoding algorithm information relating to the number of audio channels, and each of the AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute.

Preferably, if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16bits, 20bits and 24bits, said first to third sampling frequencies are respectively 48KHz, 96KHz and 192KHz, and a maximum number of said audio channels is 8.

If said audio coding mode is a compression coding system, then preferably said first to third quantization bit numbers of the audio data before compressing are respectively 16bits, 20bits and 24bits, said first to third sampling fre-

quencies are respectively 48KHz, 96KHz and 192KHz, and a maximum number of said audio channels is 8.

Said VIDEO_TS directory preferably includes information on a position of a video manager (VMG) having information on positions of said audio titles reproducible by a DVD-Video player, said VMG being recorded with the information on said audio titles, and each of said audio titles including video title set information and a plurality of contiguous video objects (VOBs).

Said VIDEO_TS directory may include information on a position of a video manager (VMG) having information on positions of said audio titles reproducible by a DVD-Video player, said VMG being recorded with the information on said audio titles, and each of said audio titles including video title set information and a plurality of contiguous video objects (VOBs).

Said VIDEO_TS directory may include information on a position of a video manager (VMG) having information on positions of said audio titles reproducible by a DVD-Video player, said VMG being recorded with the information on said audio titles, and each of said audio titles including video title set information and a plurality of contiguous video objects (VOBs).

If said audio coding mode is linear pulse code modulated (PCM) audio, a maximum number of said audio channels is preferably determined by the following Eq. 1:

$$\text{Eq. 1} \quad N = \frac{Mby}{Fs * Qb},$$

wherein Fs is the sampling frequency(Hz), Qb is the quantization bit number, Mby is the maximum data transfer rate (Mbps) of the DVD-Audio disk, and N is the maximum number of said audio channels determined by the data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

If said audio coding mode is a compression coding system, a maximum number of said audio channels is preferably determined by the following Eq. 2:

$$\text{Eq. 2} \quad N = \frac{Mby * Ccy}{Fs * Qb},$$

wherein Fs is the sampling frequency(Hz), Qb is the quantization bit number, Mby is the maximum data transfer rate (Mbps) of the DVD-Audio disk, Ccy is a compression ratio according to a DTS compression coding system and N is the maximum number of said audio channels determined by data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

Preferably, if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16bits, 20bits and 24bits, said first to third sampling frequencies are respectively 44.1KHz, 88.2KHz and 176.4KHz, a maximum of said audio channels is 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr}{Fs * Qb},$$

wherein,

Fs is the sampling frequency (Hz) of the data to be reproduced, Qb is the quantization bit number (bits) of the data to be reproduced, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, N is a maximum number of recording channels as determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

Preferably, if said audio coding mode is pseudo lossless compression coding, said first to third quantization bit numbers of the data to be reproduced before compression are respectively 16 bits, 20 bits and 24 bits, said first to third sampling frequencies are respectively 44.1KHz, 88.2KHz and 176.4KHz, a maximum number of said audio channels 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr * Ccr}{Fs * Qb},$$

wherein,

Fs is the sampling frequency (Hz) of the data to be reproduced, Qb is the quantization bit number (bits) of the data to be reproduced, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, Ccr is a compression ratio according to a DTS compression coding system, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

According to a still further aspect of the invention, there is provided a DVD-Audio disk comprising: a plurality of audio packs each including a data zone; and VIDEO_TS and AUDIO_TS directories positioned at said data zone; wherein said AUDIO_TS directory includes positional information of an audio manager (AMG), wherein the AMG stores positional information of audio titles of the DVD-Audio disk, and said audio titles include an audio title set information (ATSI) and a plurality of contiguous audio objects (AOBs); wherein each ATSI includes audio stream attributes having an audio coding mode, first, second or third quantization bits corresponding to the audio data, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the audio data and decoding algorithm information related to an audio channel number of the audio; and wherein each AOB includes the audio data corresponding to the decoding algorithm recorded on said audio stream attributes.

Preferably, if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16 bits, 20 bits and 24 bits, said first to sixth sampling frequencies are respectively 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz and 176.4KHz, a maximum number of said audio channels is 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr}{Fs \cdot Qb}$$

wherein,

Fs is the sampling frequency (Hz), Qb is the quantization bit number (bits), Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

Preferably, if said audio coding mode is pseudo lossless compression coding, said first to third quantization bit numbers of the audio data before compression are respectively 16 bits, 20 bits and 24 bits, said first to sixth sampling frequencies are respectively 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz and 176.4KHz, a maximum number of said audio channels is 8, and the number of channels is determined by the following equation:

$$N = \frac{Mbr \cdot Ccr}{Fs \cdot Qb}$$

wherein,

Fs is the sampling frequency (Hz) of the audio data, Qb is the quantization bit number (bits) of the audio data, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, Ccr is a compression ratio according to a DTS compression coding system, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

According to yet still another aspect of the invention, there is provided a DVD-Audio disk comprising: a video directory; and an audio directory; wherein both of said video and audio directories contain only audio information.

The audio information in said video directory preferably has sampling frequencies of at least one of 44.1KHz, 48KHz, 88.2KHz and 96KHz and the audio information in said audio directory has sampling frequencies of at least one of 44.1KHz, 48KHz, 88.2KHz, 96KHz, 176.4KHz and 192KHz.

The audio information in said video directory may have a sampling frequency of 96KHz, and the audio information in said audio directory may have a sampling frequency of 192KHz.

The audio information in said video directory may have a sampling frequency of 88.2KHz, and the audio information in said audio directory has a sampling frequency of 176.4KHz.

In a further aspect of the invention, there is provided a DVD-Audio disk comprising: a video title set directory; and an audio title set directory to store audio data and control data for allowing reproduction of the audio data.

The control data may comprise a logical data structure containing information on the audio data.

Said video title set directory preferably also stores audio data.

The second sampling frequency is preferably no greater than a limit of a DVD-Video standard, and the first sampling frequency is preferably above the limit.

The audio information in said video title set directory preferably has a sampling frequency of at least one of 44.1KHz, 48KHz, 88.2KHz and 96KHz and the audio information in said audio title set directory has a sampling frequency of at least one of 44.1KHz, 48KHz, 88.2KHz, 96KHz, 176.4KHz and 192KHz.

Preferably, the audio information in said video title set directory has a sampling frequency of 96KHz, and the audio information in said audio title set directory has a sampling frequency of 192KHz.

The audio information in said video title set directory may have a sampling frequency of 88.2KHz, and the audio information in said audio title set directory may have a sampling frequency of 176.4KHz.

In another aspect of the invention, there is provided an apparatus to reproduce data from a DVD, comprising: a reading unit to read the data from the disk; and a system controller to determine if an audio directory of the DVD

includes audio data and control information of the audio data, and controls reproduction of the audio data from the audio directory if the audio directory includes the audio data and the control information of the audio data.

The system controller preferably controls the reproduction of the audio data from the audio directory when the audio data from the audio directory has a sampling frequency of one of 176.4KHz and 192KHz.

5 In a further aspect of the invention, there is provided a method of reproducing data from a DVD, wherein the DVD has a video directory and an audio directory, said method comprising the steps of: determining whether audio data and control information is stored in audio directory determining that the DVD is a DVD-Audio if the audio data and control information is stored in the audio directory and that the DVD is a DVD-Video if the audio data and control information of the audio data is not stored in the audio directory; and reproducing the audio data from the audio directory
10 according to the control information if the DVD is the DVD-Audio and reproducing the audio data from the audio video directory if the DVD is the DVD-video.

Preferably, said step of reproducing the audio data comprises the steps of: determining a coding format of the audio data and selecting a corresponding decoding format if the DVD is the DVD-Audio; and reproducing the audio data using said determined decoding format if the DVD is said DVD-Audio.

15 The audio data from the audio directory of the DVD-Audio preferably has a sampling frequency of one of 176.4KHz and 192KHz, and the audio data from the video directory of the DVD-Video has a sampling frequency of one of 88.2KHz and 96KHz.

According to another aspect, an apparatus for playing the inventive DVD-Audio includes a data receiver for receiving the audio data retrieved from the DVD-Audio, a controller for generating an audio control signal containing an audio coding mode indicator, a sampling frequency, a channel number and quantization information by analyzing information on the audio data or stopping the playing operation according to whether the AUDIO_TS is detected to have effective data, an audio decoder to decode the received audio data and to multi-channel mix, sampling-frequency convert and requantize the decoded audio signal according to the audio control signal, and an audio output circuit to convert the decoded audio data into an analog audio signal.

25 According to yet another aspect, a method for playing the inventive DVD-Audio includes the steps of locating the AMG when the AUDIO_TS directory includes an effective data, checking out all information of the DVD-Audio from the information of the AMG, reading the data of the position of an audio title selected according to the position information of the AMG when receiving a command for reproducing the audio title, and setting the audio decoder to carry out the algorithm for reproducing the audio title by reading the audio stream attribute of the audio title set information management table (ATSI_AMT).

30 According to a still further aspect of the invention, there is provided an apparatus for playing a DVD-Audio disk, wherein the DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute, said apparatus comprising: a data receiver to receive said audio data retrieved from the DVD-Audio disk; a controller to generate an audio control signal including said audio coding mode, the one of said first through sixth sampling frequencies, the number of audio channels, and one of said first through third quantization bit numbers based upon information on said audio data if said Audio_TS has effective data, and, stopping a playing operation of said apparatus if said Audio_TS does not have effective data; an audio decoder to decode said audio data, to multi-channel mix, sampling-frequency convert and requantize said decoded audio signal according to said audio control signal, to generate output decoded audio data; and an audio output circuit to convert said output decoded audio data into an analog audio signal.

40 Said audio decoder preferably further comprises: a stream selector to select one of a plurality of audio streams which form said audio data according to said audio coding mode; a linear PCM decoding circuit to decode said selected audio stream if said selected audio stream is a linear PCM audio stream, and to sample frequency convert, multichannel downmix and requantize said decoded audio data according to said audio control signal; and a coding data decoding circuit to decode said selected audio stream if said selected audio stream is a compression coded audio stream using a corresponding extension algorithm, and to sample frequency convert, multichannel downmix and requantize said decoded audio data according to said audio control signal.

55 According to a yet further aspect of the invention there is provided an apparatus for playing a DVD-Audio disk and a DVD-Video disk, wherein said DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories

of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information or an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced, and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute, said DVD-Video disk including a data zone to store video data, said apparatus comprising: a data receiver to receive said audio data retrieved from said DVD-Audio disk when said DVD-Audio disk is loaded in said apparatus for reproduction, and to receive said video data retrieved from said DVD-Video when said DVD-Video disk is loaded in said apparatus for reproduction; a controller to generate an audio control signal including said audio coding mode, the one of said first through sixth sampling frequencies, the number of audio channels, and one of said first through third bit numbers quantization based upon information on said audio data if said Audio_TS has said effective data, and stopping a playing operation of said apparatus if said Audio_TS does not have said effective data; a stream parser to separate said video data and audio data output from said data receiver according to a mode control signal from said controller; a video decoding circuit to decode said video data output from said stream parser in response to said controller controlling a DVD-Video playing mode of said apparatus; a video output circuit to encode said video data output from said video decoding circuit in NTSC, and to convert said encoded video data into an analog video signal; an audio decoder having a plurality of audio decoding circuits to decode said audio data output from said stream parser by selecting a corresponding decoding circuit according to said audio coding mode, and to multi-channel mix, sampling-frequency convert and requantize said decoded audio signal according to said audio control signal, to generate an output decoded audio signal; and an audio output circuit to convert said output decoded audio signal into an analog audio signal.

Preferably, said audio decoder further comprises: a stream selector to select one of a plurality of audio streams which form said audio data according to said audio coding mode control signal to deliver said selected audio stream to the corresponding one of said plurality of audio decoding circuits; said plurality of audio decoding circuits including a linear pulse code modulated (PCM) decoding circuit to decode said selected audio stream when said selected audio stream is a linear PCM audio stream, and to sampling frequency convert, multichannel downmix and requantize said decoded linear PCM audio stream according to said audio control signal, and a coding data decoding circuit to decode said selected audio stream when said selected audio stream is a compression coded audio stream by a corresponding extension algorithm, and to sampling frequency convert, multichannel downmix and requantize said decoded compression coded audio stream according to said audio control signal.

According to yet another aspect, there is provided a method for playing a DVD-Audio disk, wherein the DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced, and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute, said method comprising the steps of: locating the AMG when the AUDIO_TS directory includes effective data; checking out other information of said DVD-Audio disk from the information of the AMG; reading position data of one of said audio titles selected according to position information of the AMG upon receiving a command for reproducing said one of said audio titles; and setting an audio decoder to carry out an algorithm for reproducing said one of said audio titles by reading the audio stream attribute of the corresponding ATSI-MAT.

A further aspect of the invention provides a DVD-Audio disk comprising: digital audio data; sampling frequency data; a maximum number of quantization bits information; and maximum data transfer rate information; wherein said digital audio data is sampled at said maximum frequency and quantized in said maximum number of bits with a number of channels of said digital audio data limited by said maximum data transfer rate.

The disk may further comprise compression ratio information of coding of said digital audio data, wherein said number of channels of said digital audio data also limited by said compression ratio information.

Said digital audio data may be coded as one of lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding.

Said lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding are preferably performed with a DTS coding system.

Said digital audio data may be coded as linear pulse code modulated (PCM) coding.

Said sampling frequency may be approximately 192KHz, said maximum bit rate is approximately 10.08 Mbps and the number of channels 8.

According to another aspect, there is provided a DVD-Audio disk comprising: a data storage area to store audio data to be reproduced, audio titles each having an audio title set management table followed by a plurality of contiguous audio objects, a plurality of audio stream attributes each having an audio coding mode, a quantization bit number, a sampling frequency and decoding algorithm information relating to a number of audio channels of said audio data, wherein each of said audio objects includes a plurality of audio packs having portions of said audio data corresponding to said decoding algorithm stored in said audio stream attribute.

Each of said audio packs may comprise: a pack header; a packet header; a sub-stream identification value; stuffing frame information; audio frame information; and one of said portions of said audio data.

Said pack header may be 14 bytes, said packet header 1 byte, said sub-stream identification value 1 byte, said stuffing frame information 1 byte, said audio frame information is 3 bytes, and said one portion of said audio data between 1 and 2013 bytes of linear pulse code modulated (PCM) data.

Each of said audio packs may comprise: a pack header; a packet header; a sub-stream identification value; audio frame information; and one of said portions of said audio data.

Said pack header may be 14 bytes, said packet header 1 byte, said sub-stream identification value 1 byte, said audio frame information 3 bytes and said one portion of said audio data between 1 and 2016 bytes of Dolby AC-3 data.

Each of said audio packs may comprise: a pack header; a packet header; and one of said portions of said audio data.

Said pack header may be 14 bytes, said packet header 1 byte, and said one portion of said audio data between 1 and 2020 bytes of MPEG data.

Each of said audio packs may comprise: a pack header; a first packet header for a main audio frame; a first one of said portions of said audio data in said main audio frame; a second packet header for an extension audio frame; and a second one of said portions of said audio data in said extension audio frame.

Said pack header may be 14 bytes, said first packet header 1 byte, said first portion of said audio data between 1 and 1152 bytes of MPEG data, said second packet header 1 byte, and said second portion of said audio data between 1 and 1584 bytes of MPEG data.

Each of said audio packs may further comprise a padding packet which is increased based upon a number of samples of said audio data.

Said sampling frequency may be approximately 48KHz, said quantization bit number 24 bits, and said number of audio channels 10, when said audio data is linear pulse code modulated (PCM) data.

A compression rate of said audio data is preferably approximately 2:1 for lossless psychoacoustic coding and approximately 4:1 for lossless pseudo psychoacoustic coding.

According to a still further aspect of the invention, there is provided an apparatus to reproduce data from the DVD, comprising: a reading unit to read the data from the disk; and a system controller to determine if an audio title set (AUDIO_TS) of the DVD includes effective data, and control reproduction of the DVD in a DVD-Audio format if said AUDIO_TS includes said effective data.

Said apparatus may further comprise: a data receiver to correct errors in the read data; an audio decoder to decode said corrected data; a digital processor to filter said decoded data; and an audio output circuit to convert said filtered data to an analog audio signal.

Preferably, said audio decoder comprises: a stream selector to determine whether said corrected data is linear pulse code modulated (PCM) coded or compression coded; a linear PCM decoder to decode said linear PCM data to processed data according to a linear PCM decoding method; a coding data decoder to decode said compression coded data to said processed data according to a corresponding compression decoding method; and a digital formatter to format said processed data as said decoded data.

Preferably, the controller controls reproduction of the DVD in a DVD-Video format if said AUDIO_TS does not include said effective data.

The apparatus may further comprise: a data receiver to correct errors in the read data; an audio/video decoder to decode said corrected data; a video output circuit to convert said decoded data to an analog video signal, if said decoded data is indicative of video information and said system controller reproduces the data of the DVD in the DVD-Video format; a digital processor to filter said decoded data if said decoded data is indicative of audio information, wherein said system controller; and an audio output circuit to convert said filtered data to an analog audio signal.

Said video output circuit encodes said decoded data in NTSC to generate said analog video data.

Preferably, said audio/video decoder comprises: a stream parser to divide said corrected data which is indicative of said video information from said corrected data which is indicative of said audio information; a video decoder to decode said corrected data indicative of said video information, to generate said decoded data indicative of said video information; and an audio decoder to decode said corrected data indicative of said audio information, to generate said decoded information indicative of said audio information.

Said audio decoder may include: a linear PCM decoder; a Dolby AC-3 decoder; a coding data decoder; and an MPEG decoder; wherein said system controller drives the corresponding one of said linear PCM decoder, Dolby AC-3 decoder, coding data decoder, and MPEG decoder, to decode said corrected data indicative of said audio information based upon a coding format of said corrected data indicative of said audio information.

Another aspect of the present invention concerns a method of reproducing data from a DVD, wherein the DVD has a data zone and an information zone, said information zone storing directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS includes information on an audio manager (AMG) which stores information on audio titles and said VIDEO_TS includes information on a video manager (VMG) which stores information on video titles, said method comprising the steps of: determining whether effective data is stored in said AUDIO_TS, and determining that the disk is a DVD-AUDIO if said effective data is stored in said AUDIO_TS and that the disk is a DVD-Video if said effective data is not stored in said AUDIO_TS; locating said AMG by reading said AUDIO_TS if the disk is said DVD-Audio; finding a designated one of said audio titles located from said AMG if the disk is said DVD-Audio; determining a coding format of said designated audio title and selecting a corresponding decoding format if the disk is said DVD-Audio; and reproducing said designated audio title using said determined decoding format if the disk is said DVD-Audio.

The method may further comprise the steps of: locating said VMG by reading said VIDEO_TS if the disk is said DVD-Video; finding a designated one of said video titles located from said VMG if the disk is said DVD-Video; and reproducing said designated video title if the disk is said DVD-Video.

Said step of reproducing said designated audio title preferably comprises the steps of: driving an audio decoding circuit to decode audio data of said audio title; determining operational state of audio decoding circuit; decoding said audio data using said audio decoding circuit, confirming said operational state of said audio decoding circuit, and outputting said decoded audio data if said operational state is normal; and stopping the drive of said audio decoding circuit, performing a repair algorithm on said audio data and restarting the drive of said audio decoding circuit, if said operational state is abnormal.

Said step of reproducing said designated audio title may comprise the steps of: driving an audio decoding circuit to decode audio data of said audio title; determining operational state of audio decoding circuit; decoding said audio data using said audio decoding circuit, confirming said operational state of said audio decoding circuit, and outputting said decoded audio data if said operational state is normal; and stopping the drive of said audio decoding circuit, performing a repair algorithm on said audio data and restarting the drive of said audio decoding circuit, if said operational state is abnormal.

For a better understanding of the invention, and to show how embodiments of the same may be carried into effect, reference will now be made, by way of example, to the accompanying diagrammatic drawings, in which:

Figure 1 is an example of the directory structure of a DVD;

Figure 2 is an example of the logical data structure of a DVD;

Figure 3 is a diagram for illustrating the structure of the video manager (VMG) and VTS;

Figure 4 is a diagram for illustrating the structure of the VMG of a DVD;

Figure 5 is a diagram for illustrating the structure of a title search pointer table (TT_SRPT) of a DVD;

Figure 6 is a diagram for illustrating the structure of a video title set information (VTSI);

Figure 7 is a diagram for illustrating the structure of a video title set management table (VTSI_MAT);

Figure 8A is a diagram for illustrating the structure of the video title set audio stream attribute table (VTS_AST_ATRT);

Figure 8B is a diagram for illustrating the internal structure of VTS_AST_ATRT;

Figure 9A is a diagram for illustrating the structure of a multi-channel audio stream attribute table of a video title set (VTS_MU_AST_ATRT);

Figure 9B is a diagram for illustrating the structure of a multi-channel audio stream attribute (1) of a video title set (VTS_MU_AST_ATR(1));

Figures 9C and 9D are diagrams for illustrating the structure of the VTS_MU_AST_ATR(2);

Figure 10 is a diagram for illustrating a logical structure of the DVD-Audio;

5 Figure 11 is a diagram for illustrating the structures of an audio manager (AMG) and audio title set (ATS) of the DVD-Audio;

Figure 12 is a diagram for illustrating the structure of an audio manager information (AMGI) of the DVD-Audio;

10 Figure 13 is a diagram for illustrating the structure of a title search pointer table (TT_SRPT) of the DVD-Audio;

Figure 14 is a diagram for illustrating the structure of an audio title set information (ATSI) of the DVD-Audio;

15 Figure 15 is a diagram for illustrating the structure of an audio title set information management table (ATSI_MAT) of the DVD-Audio;

Figure 16 is a diagram for illustrating the internal structure of an audio stream attribute of an audio title set menu (ATSM_AST_ATR) of the DVD-Audio;

20 Figure 17A is a diagram for illustrating the structure of an audio stream attribute table of an audio title set (ATS_AST_ATRT) of the DVD-Audio;

25 Figure 17B is a diagram for illustrating the structure of an audio stream attribute of an audio title set (ATS_AST_ATR) of the DVD-Audio;

Figure 18A is a diagram for illustrating the structure of a multi-channel audio stream attribute of an audio title set (ATS_MU_AST_ATR) of the DVD-Audio;

30 Figure 18B is a diagram for illustrating the structure of a first extension of a multi-channel audio stream attribute of an audio title set (ATS_MU_AST_ATR_EXT(1)) of the DVD-Audio;

Figure 18C is a diagram for illustrating the structure of a second extension of a multi-channel audio stream attribute of the audio title set (ATS_MU_AST_ATR_EXT(2)) of the DVD-Audio;

35 Figure 19 is a diagram for illustrating the structure of an audio object set (AOBS) of the DVD-Audio;

Figure 20 is a diagram for illustrating a pack structure of the DVD-Audio;

40 Figures 21A to 21D are diagrams for illustrating various pack structures of the DVD-Audio;

Figure 22 is a diagram for illustrating a linear PCM audio packet in the audio pack as shown in Figure 21A;

Figure 23 is a diagram for illustrating the structure of a linear PCMA audio frame of the DVD-Audio;

45 Figures 24A to 24C are diagrams for illustrating a sample data arrangement of the linear PCM;

Figure 25 is a diagram for illustrating the structure of a linear audio packet of the DVD-Audio;

50 Figure 26 is a diagram for illustrating the structure of a DTS audio packet of the DVD-Audio;

Figure 27 is a block diagram for illustrating the functional structure of a DVD-Audio player according to a first embodiment of the present invention;

55 Figure 28 is a block diagram for illustrating the structure of an audio decoder as shown in Figure 27;

Figure 29 is a block diagram for illustrating the functional structure of a DVD-Audio/DVD-Video player according to a second embodiment of the present invention;

Figure 30 is a block diagram for illustrating the structure of an audio/video decoder as shown in Figure 29;

Figure 31 is a flow chart for illustrating the process of reproducing audio data from a DVD-Audio in the DVD-Audio player; and

Figure 32 is a flow chart for illustrating the operation of an audio decoder in the DVD-Audio player.

In the attached drawings, the same reference numerals are used to represent parts serving the same functions and detailed descriptions are omitted concerning the parts not essential to describe the inventive concept, for convenience's sake.

The data structure of the DVD-Audio is similar to that of the DVD-Video. Hence, the DVD-Audio includes a data zone to record the audio data and an information zone to record the information on the audio data. The DVD player may be embodied in the form of a DVD-Audio player or a DVD-Audio/Video player. Of course, the DVD player has a mechanism to determine whether an inserted DVD is a DVD-Audio or DVD-Video. The inventive DVD-Audio has almost the same structure as the DVD-Video with some partly changed data structure to achieve the audio data of high quality.

The fundamental file structure recorded in the information zone of the DVD-Audio is as shown in Figure 1 for illustrating a directory structure for the DVD-Video and DVD-Audio. The directory structure generally includes a video title set directory (VIDEO_TS), audio title set directory (AUDIO_TS) and a user defined directory. Each of the directories contains a plurality of files of which the names shall be assigned. The directory structure is to represent the locations of the files in the disk. The files connected to the VIDEO_TS are prepared for the DVD-Video and DVD-Video player while those connected to the AUDIO_TS are prepared for the DVD-Audio and DVD-Audio player.

Generally, each of the DVD-Video and DVD-Audio contains both VIDEO_TS and AUDIO_TS. However, the DVD-Video has the AUDIO_TS emptied (all of the information on the data stored in the DVD-Video disk being contained in the VIDEO_TS) while the DVD-Audio has the AUDIO_TS containing the information on the positions of the audio titles recorded on the disk and the VIDEO_TS also containing the information on the positions of the titles of reproducible information (spec: e.g., sampling frequency) in the DVD-Video player. Hence, if a DVD has no effective data in the AUDIO_TS, it is determined as being DVD-Video, or otherwise, i.e., if the DVD player detects effective data in the AUDIO_TS, it determines the disk as being DVD-Audio. Namely, the DVD player detects the AUDIO_TS of a DVD to distinguish DVD-Video and DVD-Audio.

The logical data structure of DVD-Video is illustrated in Figure 1. The concept of the logical data structure of DVD-Video includes structure of a volume space, structure of a video manager (VMG), structure of a video title set (VTS), and structure of a video object set (VOBS).

Describing the logical data structure of the volume space with reference to Figure 2, it includes the volume and file structure, single DVD-Video zone and DVD others zone. The DVD-Video zone, which shall be assigned for the data structure of the DVD-Video, includes a single VMG and VTSs numbering from at least 1 to a maximum of 99. The VMG is allocated at the leading part of the DVD-Video zone. Each VTS includes between 3 and 12 files.

Referring to Figure 3 for illustrating the VMG and VTS structure, all VOBs are recorded in contiguous blocks. Each VOB includes video, audio and sub-picture data. The VMG includes a video manager information file (VMGI) as control data, video manager menu file of the VOBs (VMGM_VOBS) and VMGI backup file. Each VTS includes VTSI as control data, a video title set menu of VOBs (VTSM_VOBS), a video title set title of VOBs (VTSTT_VOBS) and a VTSI backup file. The VTSTT_VOBS includes a plurality of cells (C_IDN). In the drawing, C_IDN# indicates cell ID number within a VOBs, and VOB_IDN# VOB ID number within a VOBs.

Referring to Figure 4, the VMGI describes information on the related VIDEO_TS directory. The VMGI starts with a video manager information management table (VMGI_MAT), followed by a title search pointer table (TT_SRPT), followed by a video manager menu PGCI unit table (VMGM_PGCI_UT), followed by a parental management information table (PTL_MAIT), followed by a video title set attribute table (VTS_ATRT), followed by a text data manager (TXTDT_MG), followed by a video manager menu cell address table (VMGM_C_ADT), followed by a video manager menu video object unit address map (VMGM_VOBU_ADMAP).

Referring to Figure 5 for describing search information of a video title under the VIDEO_TS directory, the TT_SRPT starts with TT_SRPT information (TT_SRPTI) followed by title search pointers (TT_SRP) for every title under the VIDEO_TS directory. The title number # ranges from 1 to 99.

Referring to Figure 6, the VTSI provides information for one or more video titles and the video title set menu (VTSM). The VTSI describes the management information of these titles such as the information to search the part_of title (PTT) and the information to play back the video object set (VOBS), and the video title set menu (VTSM), as well as the information on the attribute of the VOBs.

The VTSI starts with a video title set information management table (VTSI_MAT), followed by a video title set part_of title search pointer table (VTS_PTT_SPRT), followed by a video title set program chain information table (VTS_PGCIT), followed by a video title set menu PGCI unit table (VTSM_PGCI_UT), followed by a video title set time

EP 0 867 877 A2

map table (VTS_TMAPT), followed by a video title set menu cell address table (VTSM_C_ADT), followed by a video title set menu video object unit address map (VTSM_VOBU_ADMAP), followed by a video title set cell address table (VTS_C_ADT), followed by a video title set video object unit address map (VTS_VOBU_ADMAP) as shown in Figure 6.

Referring to Figure 7, the VTSI_MAT describes the start address of each piece of information in the VTSI and the attribute of the VOBS in the VTS. In this VTSI_MAT, the audio stream attribute table of the VTS (VTS_AST_ATRT) of RBP 516 to 579 stores 8 VTS_AST_ATRs #0 to #7 as shown in Figure 8A. Each VTS_AST_ATR includes 8 bytes arranged as shown in Figure 8B. Each field value represents the internal information of the audio stream of the VTSM_VOBS. Describing the contents of one VTS_AST_ATR with reference to Figure 8B, the audio coding mode of b63 to b61 is as shown in the following Table 1:

Table 1

b63-b61	Audio Coding Mode
000b	Dolby AC-3
010b	MPEG-1 or MPEG-2 without extension bit stream
011b	MPEG-2 with extension bitstream
100b	Linear PCM audio
110b	DTS (option)
111b	SDDS (option)
Others	reserved

The multichannel extension of b60 is to store information on whether the multichannel extension is made or not. Namely, 0b represents the multichannel extension not selected while 1b represents the multichannel extension selected according to the information of the VTS_MU_AST_ATRT recorded in RBP 792 to 983 of the VTSI_MAT shown in Figure 7.

The audio type of b59 to b58 is as shown in Table 2.

Table 2

b59-b58	audio type
00b	Not specified
01b	Language included
others	reserved

The audio application mode of b57 to b56 is as shown in the following Table 3.

Table 3

b57-b56	audio application mode
00b	Not specified
01b	Karaoke mode
10b	Surround mode
11b	reserved

For the quantization /DRC of b55 to b54, when the audio coding mode is '000b', '11b' is recorded. When the audio coding mode is '010b' or '011b', the quantization / DRC is defined as:

00b: Dynamic range control data do not exist in MPEG audio stream

01b: Dynamic range control data exist in MPEG audio stream

10b: reserved

11b: reserved

When the audio coding mode '100b', then the quantization / DRC is defined as in the following Table 4.

Table 4

b55-b54	Quantization DRC
00b	16bits
01b	20bits
10b	24bits
11b	reserved

The sampling frequency fs of b53 to b52 is as shown in Table 5.

Table 5

b53-b52	fs
00b	48KHz
01b	96KHz
10b	reserved
11b	reserved

The number of audio channels stored in b50 to b48 is as shown in Table 6.

Table 6

b50-b48	No. of Audio Channels
000b	1ch (mono)
001b	2ch (stereo)
010b	3ch (multichannel)
011b	4ch (multichannel)
100b	5ch (multichannel)
101b	6ch (multichannel)
110b	7ch (multichannel)
111b	8ch (multichannel)
others	reserved

In addition, the multichannel audio stream attribute table of the VTS of RBP 792 to 983 in the VTSI_MAT of Figure 7 provides the VTS_MU_AST_ATRs #0 to #7 of 8 audio streams as shown in Figure 9A. Each VTS_MU_AST_ATR includes a VTS_MU_AST_ATR (1) of 8 bytes as shown in Figure 9B and a VTS_MU_AST_ATR (2) of 16 bytes as shown in Figures 9C and 9D.

Thus, the information zone VIDEO_TS of the DVD-Video is constructed as shown in Figures 2 to 9D. Such a DVD-Video stores both video and audio data, and therefore can not provide audio data of good quality. Hence, it is impossible to record the audio data on a DVD-Video at the maximum rate 10.08Mbps of the DVD. Namely, the maximum bit rate to record the audio data on the DVD-Video is 6.75Mbps, and the maximum sampling frequency 96KHz. The linear PCM multichannel audio data recorded on the DVD-Video is as shown in Table 7.

Table 7

fs	Qb	Maximum Number of Channels	Maximum Bit Rate
48KHz	16bit	8ch	6.144Mbps

Table 7 (continued)

fs	Qb	Maximum Number of Channels	Maximum Bit Rate
48KHz	20bit	6ch	5.760Mbps
48KHz	24bit	5ch	5.760Mbps
96KHz	16bit	4ch	6.144Mbps
96KHz	20bit	3ch	5.760Mbps
96KHz	24bit	2ch	4.608Mbps

The present invention is to provide a DVD-Audio for recording only audio data not including video data. Hence, the DVD-Audio can store multichannel audio data in the range of the maximum bit rate 10.08Mbps of the DVD, which is different from the DVD-Video. Thus, the DVD-Audio may use the sampling frequency of at most 192KHz, and extend the number of the audio channels to 13.

The file structure stored in the information zone of the DVD-Audio is essentially the same as shown in Figure 1. The files included in the AUDIO_TS directory are to provide for the DVD-Audio and its player. Hence, the DVD-Audio has both AUDIO_TS and VIDEO_TS, where the VIDEO_TS stores the positional information of the VMG and titles which are reproducible in a DVD-Video player. The AUDIO_TS stores the positional information of the AMG and titles which are reproducible in a DVD-Audio player. The DVD player determines whether an inserted DVD is DVD-Audio or not by checking the contents of the audio title set directory AUDIO_TS.

Referring to Figure 10, the logical data structure of the DVD-Audio includes structure of a volume space, structure of an audio manager (AMG), structure of an audio title set (ATS), and structure of an audio object set (AOBS). The volume space includes the volume and file structure, a single DVD-Audio zone and DVD others zone. The DVD-Audio zone, which is assigned for the data structure of the DVD-Audio, includes a single AMG and VTSS numbering from at least 1 to a maximum of 99. The AMG is allocated at the leading part of the DVD-Audio zone, including 2 or 3 files. Each VTS includes between 3 and 12 files.

The AMG and ATS are structured similar to the VMG and VTS of the DVD-Video, as shown in Figures 11-17C. However, the data structure for the linear PCM and pseudo-lossless psychoacoustic coded data (PLPCD) of the DVD-Audio is not proper for processing the linear PCM, lossless coded data or PLPCD according to the new sampling frequency of the DVD-Audio. Therefore, the data structures of the AMG and ATS are made somewhat different from that of the VMG and VTS. Namely, the part allocated for the sampling frequency and channel number in the part allocated for the audio attribute of the VMG and VTS is extended for the AMG and ATS.

Referring to Figure 11 for illustrating the AMG and ATS structures, all AOBs are recorded in contiguous blocks. The AMG includes an audio manager information file (AMGI) as control data, an audio manager menu file of the AOBs (AMGM_AOBS) and an AGMI backup file. Each ATS includes ATSI as control data, an audio title set menu of AOBs (ATSM_AOBS), an audio title set title of AOBs (ATSTT_AOBS) and an ATSI backup file. The ATSTT_AOBS includes a plurality of cells (C_IDN). In the drawing, C_IDN# indicates cell ID number within an AOBs, and AOB_IDN# AOB ID number within an AOBs.

Referring to Figure 12, the AMGI describes information on the related AUDIO_TS directory. The AMGI starts with an audio manager information management table (AMGI_MAT), followed by a title search pointer table (TT_SRPT), followed by an audio manager menu PGCI unit table (AMGM_PGCI_UT), followed by a parental management information table (PTL_MAIT), followed by an audio title set attribute table (ATS_ATRT), followed by a text data manager (TXTDT_MG), followed by an audio manager menu cell address table (AMGM_C_ADT), followed by an audio manager menu audio object unit address map (AMGM_AOBU_ADMAP).

Referring to Figure 13 for describing search information of an audio title under the VIDEO_TS directory, the TT_SRPT starts with TT SRPT information (TT_SRPTI) followed by title search pointers (TT SRPs) for every title under the AUDIO_TS directory. The title number # ranges from 1 to 99.

Referring to Figure 14, the ATSI provides information for one or more audio titles and audio title set menu (ATSM). The ATSI describes the management information of these titles such as the information to search the part_of title (PTT) and the information to play back the audio object set (AOBS), and the audio title set menu (ATSM), as well as the information on the attribute of the AOBs.

The ATSI starts with audio title set information management table (ATSI_MAT), followed by an audio title set part_of_title search pointer table (ATS_PTT_SPRT), followed by an audio title set program chain information table (ATS_PGCI_T), followed by an audio title set menu PGCI unit table (ATSM_PGCI_UT), followed by an audio title set time map table (ATS_TMPT), followed by an audio title set menu cell address table (ATSM_C_ADT), followed by an audio title set menu audio object unit address map (ATSM_AOBU_ADMAP), followed by an audio title set cell address

table (ATS_C_ADT), followed by an audio title set audio object unit address map (ATS_AOBU_ADMAP) as shown in Figure 14.

Referring to Figure 15, the ATSI_MAT describes the start address of each information in the ATSI and the attribute of the AOBs in the ATS. The ATSI_MAT is provided with ATSM_AST_ATR of RBP 260 to 267, ATS_AST_ATRT of RBP 516 to 579 and ATS_MU_AST_ATR_EXT of RBP 792 to 1298.

The audio coding mode of the ATSM_AST_ATR and ATS_AST_ATRT stores the coding information of the audio data recorded in the DVD-Audio. The present embodiment describes the recording on the DVD-Audio of the audio data of lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding (hereinafter referred to as "psychoacoustic coding"). In addition, it is assumed that the psychoacoustic coding mode is performed with a DTS coding system, which may support the lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding. In this case, the DTS coding mode is optional, and if b63 to b61 is '110b', the DTS audio coding mode is selected.

For the change of ATSM_AST_ATR, the data pattern and definition of b55 to b48 are changed. Namely, the sampling frequency data of b53 to b52 is changed, and the reserved bit of b51 is included in the audio channels, as shown in Figure 16. Thus, the audio sampling frequency fs is changed as shown in Table 8.

Table 8

b53-b52	b51	fs
00b	0	48KHZ
01b	0	96KHz
10b	0	192KHz
11b	0	reserved
00b	1	44.1KHz
01b	1	88.2KHz
10b	1	176.4KHz
11b	1	reserved

In addition, the number of the audio channels is changed as shown in Tables 9a and 9b.

Table 9a

b51-b48	Number of Audio Channels
0000b	1ch (mono)
0001b	2ch (stereo)
0010b	3ch (multichannel)
0011b	4ch (multichannel)
0100b	5ch (multichannel)
0101b	6ch (multichannel)
0110b	7ch (multichannel)
0111b	8ch (multichannel)
1000b	9ch (multichannel)
1001b	10ch (multichannel)
1010b	11ch (multichannel)
1011b	12ch (multichannel)

Table 9b

1100b	13ch (multichannel)
1101b	14ch (multichannel)

Table 9b (continued)

1110b	15ch (multichannel)
1111b	16ch (multichannel)

The ATS_AST_ATRT of RBP 516 to 579 in the ATSI_MAT as shown in Figure 15 stores ATS_AST_ATRs of 8 audio streams #0 to #7 as shown in Figure 17A, each of which includes 8 bytes structured as shown in Figure 17B, and each field value serves as the internal information of the audio stream of the ATSM_AOBS.

The data pattern and definition of b55 to b48 are changed as shown in Figure 17B. Namely, in b55 to b48 of the VTS_AST_ATRT as shown in Figure 8B, the reserved bit of b51 is included in the audio channels. Consequently, the audio sampling frequency f_s is changed as shown in Table 8 while the number of the audio channels is changed as shown in Tables 9a and 9b.

In the ATS_MU_AST_ATRT, the information as shown in Figures 18B and 18C are added to the information of Figures 9B and 9C. The ATS_MU_AST_ATR(1) and ATS_MU_AST_ATR(2) provide the information on the audio data and channel mixing coefficients up to 8 channels, and therefore can not provide the information on the linear PCM audio over 8 channels. The present invention may provide up to 13 channels, so that the information from the 9th channel to the 13th channel are recorded in the reserved regions after the ATS_MU_AST_ATR(1) and ATS_MU_AST_ATR(2). Referring to Figure 18A, the ATS_MU_AST_ATRT provides 13 ATS_MU_AST_ATRs #0 to #12 each having 39 bytes to store the information on 13 audio channels and the mixing coefficients.

Each ATS_MU_AST_ATR includes the audio channel information as shown in Figure 18B and the mixing coefficient information as shown in Figure 18C. Figure 18B illustrates only the information of the extended five audio channels ATS_MU_AST_ATR_EXT(1), while omitting the ATS_MU_AST_ATR(1) for storing the data information of the 8 audio channels. Likewise, Figure 18C illustrates only the information of the extended five audio channels ATS_MU_AST_ATR_EXT(2), while omitting the ATS_MU_AST_ATR(2) for storing the data information of the 8 audio channels.

The ATSI_MAT represents the information on the audio data recorded on the DVD-Audio, forming the first part of each audio title and followed by the AOBS of substantial audio data. Of course, the VTSI_MAT as shown in Figure 7 represent also the information on the video data, sub-picture data and audio data recorded on the DVD-Video, forming the first part of each video title and followed by the VOBS of substantial data. The AOBS is structured as shown in Figure 19, providing a plurality of audio packs to store the audio data. Likewise, the VOBS is structured similar to Figure 19, providing a plurality of video packs, sub-picture packs and audio packs to respectively store the video data, sub-picture data and audio data.

The structure of the AOBS is similar to that of the VOBS, and therefore description of the structure of the VOBS will help understand the structure of the AOBS. The VOBS includes a plurality of video objects VOB_IDN1 to VOB_IDNi, each of which in turn includes a plurality of cells C_IDN1 to C_IDNi, each of which in turn includes a plurality of video object units VOBUs, each of which in turn includes a plurality of video packs.

The video data recorded in a DVD-Video includes a plurality of packs, whose structure is illustrated in Figure 20 without a padding packet. Referring to Figure 20, one pack has a size of 2048 bytes including a pack header of 14 bytes and a plurality of packets for video, audio, sub-picture, DSI or PCI of 2034 bytes. Further, the packet header includes a pack start code of 4 bytes, SCR of 6 bytes, program_mux_rate of 3 bytes and stuffing_length of 1 byte.

Referring to Figure 21A, the linear PCM audio pack includes a pack header of 14 bytes and a linear audio packet of 2034 bytes. The audio packet includes a packet header of 1 byte, sub_stream_id of 1 byte, audio frame information of 3 bytes and linear PCM audio data of 1 to 2013 bytes.

Referring to Figure 21B, the dolby AC-3 audio pack includes a pack header of 14 bytes and a dolby AC-3 audio packet of 2034 bytes. The audio packet further includes a packet header of 1 byte, sub_stream_id of 1 byte, audio frame information of 3 bytes and AC-3 audio data of 1 to 2016 bytes.

Figure 21C illustrates the structure of an MPEG-1 or MPEG-2 audio pack without an extension bit stream, and Figure 21D the structure of MPEG-2 with an extension stream. The structures of the audio packs as shown in Figs 21A to 21D are shown in Table 10, additionally provided with private data areas corresponding to their formats.

Table 10

Field	Bit	Byte	Value	Comment
packet_start_code_prefix	24	3	00 0001h	
stream_id	8	1	1011 1101b	private_stream_1
PES_packet_length	16	2		

EP 0 867 877 A2

Table 10 (continued)

Field	Bit	Byte	Value	Comment
'10'	2	3		
PES_scrambling_control	2	3	00b	not scrambled
PES_priority	1	3	0	no priority
data_alignment_indicator	1	3	0	not defined by descriptor
copyright	1	3	0	not defined by descriptor
original_or_copy	1	3	1 or 0	original:1 copy:0
PTS_DTS_flags	2	3	10 or 00b	
ESCR_flag	1	3	0	no ESCR field
ES_rate_flag	1	3	0	no EST rate field
DSTM_trick_mode_flag	1	3	0	no trick mode field
additional_copy_info_flag	1	3	0	no copy info field
PES_CRC_flag	1	3	0	no CRC field
PES_extension_flag	1	3	0 or 1	
PES_header_data_length	8	3	0 to 15	
'0010'	4	5	provider defined	Note 1
PTS[32...30]	3	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[29...15]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[14...0]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PES_private_data_flag	1	1	0	Note 2
pack_header_field_flag	1	1	0	Note 2
program_packet_sequence_counter_flag	1	1	0	Note 2
P_STD_buffer_flag	1	1	1	Note 2
reserved	3	1	111b	Note 2
PES_extension_flag_2	1	1	0	Note 2
'01'	2	2	01b	Note 2
P_STD_buffer_scale	1	2	1	Note 2
P_STD_buffer_size	13	2	58	Note 2
stuffing_byte	-	0-7		

In Table 10, Notes 1 and 2 are described as follows:

Note 1: "PTS[32...0]" shall be described in every audio packet in which the first sample of an audio frame is included.

Note 2: These fields occur in the first audio packet of each VOB, and are prohibited in the subsequent audio packets.

In the audio packet of the linear PCM data structured as shown in Figure 21A, the data recorded in the private data area besides the common data area is as shown in Table 11.

Table 11

5	Field	Bit	Byte	Value	Comment
	sub_stream_id	8	1	10100***b	Note 1
10	number_of_frame_headers	8	3	Provider Defined	Note 2
	first_access_unit_pointer	16			Note 3
	audio_emphasis_flag	1			Note 4
15	audio_mute_flag	1			Note 5
	reserved	1			0
20	audio_frame_number	5		Provider Defined	Note 6
	quantization_word_length	2			Note 7
	audio sampling frequency	2			Note 8
25	reserved	1		0	
	number_of_audio_channels	3		Provider Defined	Note 9
30	dynamic_range_control	8			Note 10
Audio Data Area (Linear PCM)					

35 In Table 11, Notes 1 to 10 are described as follows:

Note 1: *** represents decoding an audio data stream number.

40 Note 2: "number_of frame_headers" describes the number of audio frames whose first byte is in this audio packet.

Note 3: The access unit is the audio frame. The first access unit is the first audio frame which has the first byte of the audio frame.

45 Note 4: "audio_emphasis_flag" describes the state of emphasis. When "audio_sampling_frequency" is 96KHz, "emphasis off" is described in this field. The emphasis is applied to all audio samples decoded from the first access unit.

0b: emphasis off

50 1b: emphasis on

Note 5: "audio_mute_flag" describes the state of mute while all data in the audio frame is ZERO. The mute is applied to all audio samples decoded from the first access unit.

55 Note 6: "audio_frame_number" describes the frame number of the first access unit in the Group of audio frame (GOF) with the numbers between '0' and '19'.

Note 7: "quantization_word_length" describes the word-length which the audio samples are quantized to.

00b: 16 bits

01b: 20 bits

5 10b: 24 bits

11b: reserved

Note 8: "audio_sampling_frequency" describes the sampling frequency of the audio sample.

10

00b: 48KHz

01b: 96KHz

15

Others: reserved

Note 9: "number_of_channels" describes the number of audio channels.

20

000b: 1ch (mono)

001b: 2ch (stereo)

25

010b: 3ch	}	(multichannel)
011b: 4ch		
100b: 5ch		
101b: 6ch		
110b: 7ch		
111b: 8ch		

30

Note 10: "dynamic_range_control" describes the dynamic word control word to compress the dynamic range from the first access unit.

35

In the audio packets as shown in Figures 21A to 21D, the stream_id of the linear PCM audio packet is 1011 1101b (private_stream_1), and the sub_stream_id 1010 0***b. The stream_id of the AC-3 audio packet is 1011 1101b (private_stream_1), and the sub_stream_id 1000 0***b. The stream_id of the MPEG audio packet is 1100 0***b or 1101 0***b, and no sub_stream_id. ***** in the stream_id or sub stream id indicates the decoding audio stream number which has a value between "0" and "7", and the decoding audio stream numbers are not assigned the same number regardless of the audio compression mode.

40

Figure 22 illustrates the structure of the audio stream and packs. The audio data used in the DVD-Audio may include linear PCM data, dolby AC-3 data and MPEG audio data. The audio stream further includes a plurality of audio packs. In addition, each audio pack constitutes a unit of 2048 bytes as shown in Figure 22. In this case, the form of encoding the linear PCM audio is based on Table 12.

45

Table 12

Sampling frequency(fs)	48KHz	96KHz
Sampling Phase	Shall be simultaneous for all channels in a stream	
Quantization	16 bits or more, 2's complementary code	
Emphasis	Can be applied (zero point: 50μs, pole: 15μs)	Can not be applied

50

In Table 12, the audio stream data for linear PCM includes contiguous GOFs (Group of Audio Frames), each of which includes 20 audio frames except for the last GOF. The last GOF includes no more than 20 audio frames.

55

Figure 23 illustrates the structure of the audio frame. One audio frame includes sample data which correspond to the presentation time of 1/600 second. One audio frame contains 80 or 160 audio sample data according to a frequency (fs) of 48KHz or 96KHz. One GOF corresponds to the presentation time of 1/30 second.

Figures 24A to 24C illustrate a sample data alignment for linear PCM. Sample data is formed by the data from each channel sampled out at the same time. Therefore, the size of sample data varies with the audio stream attribute. The sampled data is continuously arranged. Two sample data for each mode are shown in Figures 24A to 24C. Figure 24A illustrates a 16 bits mode, Figure 24B illustrates a 20 bits mode and Figure 24C illustrates a 24 bits mode. The packet data structure of the linear PCM audio is as shown in Table 13.

Table 13

Stream Mode			Data in a Packet			
Number of Channels	fs (KHz)	Quantization	Maximum number of samples in a packet	Data size (byte)	Packet Stuffing of first/other PES packet (byte)	Padding packet for first/other PES packet (byte)
1 mono	48/96	16	1004	2008	2/5	0/0
	48/96	20	804	2010	0/3	0/0
	48/96	24	670	2010	0/3	0/0
2 stereo	48/96	16	502	2008	2/5	0/0
	48/96	20	402	2010	0/3	0/0
	48/96	24	334	2004	6/0	0/9
3	48/96	16	334	2004	6/0	0/9
	48/96	20	268	2010	0/3	0/0
	48	24	222	1988	0/0	12/15
4	48/96	16	250	2000	0/0	10/13
	48	20	200	2000	0/0	10/13
	48	24	166	1992	0/0	18/21
5	48	16	200	2000	0/0	10/13
	48	20	160	2000	0/0	10/13
	48	24	134	2010	0/3	0/0
6	48	16	166	1992	0/0	18/21
	48	20	134	2010	0/3	0/0
7	48	16	142	1988	0/0	22/25
8	48	16	124	1984	0/0	26/29

If the number of samples is less than in Table 13, the length of a padding packet may increase to adjust the pack size. Samples shall be aligned at packet boundary. Namely, the audio sample data of every audio packet for linear PCM audio always start with the first byte of S_{2n} described in Table 13. The channel assignment for linear PCM is as follows:

In the stereo presentation mode, the descriptions of channels, ACH0 and ACH1 correspond to left channel (L-ch) and right channel (R-ch) respectively. Multichannel coding is required to keep compatibility with the stereo mode.

The structure of the DVD-Audio is as shown in Figure 19. Since the DVD-Audio is to store audio data, it contains no video pack (V_PCK) or sub-picture pack (SP_PCK), or otherwise only small amounts of them. The AOBS includes a plurality of packs of data as the VOBS does. The general structure of the audio pack is as shown in Figures 20 and 21A to 21D. It is assumed that the inventive DVD-Audio does not employ MPEG and AC-3 and instead records audio data of linear PCM and compression coding system.

Tables 10 and 11 illustrate the linear PCM audio packet of the DVD-Video, which may be altered to obtain the linear PCM audio packet of the DVD-Audio. Describing the linear PCM system of the DVD-Audio, the sampling frequencies are 48, 44.1, 96, 188.2, 192 or 176.4KHz, the number of quantization bits is 16, 20 or 24 bits, and the number of audio channels is from 1ch to the maximum allowed by the bit rate. The number of the audio channels may be

determined by Eq. 1.

$$\text{Eq. 1} \quad N = \frac{M_{by}}{F_s \cdot Q_b}$$

F_s: Sampling Frequency(Hz) → 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz, or 176.4KHz.

Q_b: Number of Quantization Bits → 16bits, 20bits, 24bits M_{by}: Maximum Data Transfer Rate of DVD(Mbps) → 10.08Mbps N: Maximum Number of Possible Channels Determined by Data Transmission Rate, Sampling Frequency and Number of Quantization Bits of DVD.

The number of channels determined by Eq. 1 is shown in Table 14.

Table 14

Sampling Frequency	Number of Quantization Bits	Maximum Number of Channels
48KHz/44.1KHz	16 bits	8
48KHz/44.1KHz	20	8
48KHz/44.1KHz	24	8
96KHz/88.2KHz	16	6
96KHz/88.2KHz	20	5
96KHz/88.2KHz	24	4
192KHz/176.4KHz	16	3
192KHz/176.4KHz	20	2
192KHz/176.4KHz	24	2

The structure of the linear PCM audio pack of the DVD-Audio is constructed as shown in Figure 25, which is the same as that of the DVD-Video as shown in Figure 21A. Namely, one audio pack comprises a pack header of 14 bytes and one or more linear PCM packets of at maximum 2021 bytes. The pack header is based on an MPEG2 system layer.

The structure of the linear PCM audio packet is also based on the MPEG2 system layer. The linear PCM audio packet is constructed as shown in Tables 15 and 16. Table 15 has the same structure as Table 10 while Table 16 for representing private data structure has a structure different from that of Table 11.

Table 15

Field	Bit	Byte	Value	Comment
packet_start_code_prefix	24	3	00 0001h	
stream_id	8	1	1011 1101b	private_stream_1
PES_packet_length	16	2		
'10'	2	3		
PES_scrambling_control	2	3	00b	not scrambled
PES_priority	1	3	0	no priority
data_alignment_indicator	1	3	0	not defined by descriptor
copyright	1	3	0	not defined by descriptor
original_or_copy	1	3	1 or 0	original:1 copy:0
PTS_DTS_flags	2	3	10 or 00b	
ESCR_flag	1	3	0	no ESCR field
ES_rate_flag	1	3	0	no EST rate field
DSTM_trick_mode_flag	1	3	0	no trick mode field
additional_copy_info_flag	1	3	0	no copy info field

EP 0 867 877 A2

Table 15 (continued)

Field	Bit	Byte	Value	Comment
PES_CRC_flag	1	3	0	no CRC field
PES_extension_flag	1	3	0 or 1	
PES_header_data_length	8	3	0 to 15	
'0010'	4	5	provider defined	Note 1
PTS[32...30]	3	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[29...15]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[14...0]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PES_private_data_flag	1	1	0	Note 2
pack_header_field_flag	1	1	0	Note 2
program_packet_sequence_counter_flag	1	1	0	Note 2
P_STD_buffer_flag	1	1	1	Note 2
reserved	3	1	111b	Note 2
PES_extension_flag_2	1	1	0	Note 2
'01'	2	2	01b	Note 2
P_STD_buffer_scale	1	2	1	Note 2
P_STD_buffer_size	13	2	58	Note 2
stuffing_byte	-	0-7		

Table 16

35

Field	Bit	Byte	Value	Comment
sub_stream_id	8	1	10100***b	Note 1
number_of_frame_headers	8	3	Provider Defined	Note 2
first_access_unit_pointer	16		Provider Defined	Note 3
audio_emphasis_flag	1		Provider Defined	Note 4
audio_mute_flag	1		Provider Defined	Note 5
reserved	1		0	
audio_frame_number	5		Provider Defined	Note 6
quantization_word_length	2		Provider Defined	Note 7
audio_sampling_frequency	3		Provider Defined	Note 8
number_of_audio_channels	3		Provider Defined	Note 9
dynamic_range_control	8		Provider Defined	Note 10
Audio Data Area (Linear PCM)				

40

45

50

In Table 16, Notes 1 to 10 are described as follows:

Note 1: *** represents decoding the audio data stream number.

EP 0 867 877 A2

Note 2: "number_of_frame_headers" describes the number of audio frames whose first byte is in this audio packet.

Note 3: The access unit is the audio frame. The first access unit is the first audio frame which has the first byte of the audio frame.

5

Note 4: "audio_emphasis_flag" describes the state of emphasis. When "audio_sampling_frequency" is 96KHz, "emphasis off" is described in this field. The emphasis is applied to all audio samples decoded from the first access unit.

10

0b: emphasis off

1b: emphasis on

15

Note 5: "audio_mute_flag" describes the state of mute while all data in the audio frame is ZERO. The mute is applied to all audio samples decoded from the first access unit.

0b: mute off

1b: mute on

20

Note 6: "audio_frame_number" describes the frame number of the first access unit in the Group of audio frame (GOF) with the numbers between '0' and '19'.

25

Note 7: "quantization_word_length" describes the word-length which the audio samples are quantized to.

00b: 16 bits

01b: 20 bits

30

10b: 24 bits

11b: reserved

35

Note 8: "audio_sampling_frequency" describes the sampling frequency of the audio sample.

00b: 48KHz

01b: 96KHz

40

10b: 192KHz

11b: reserved

45

100b: 44.1KHz

101b: 88.2KHz

110b: 176.4KHz

50

111b: reserved

Note 9: "number_of_channels" describes the number of audio channels.

55

0000b: 1ch (mono)

0001b: 2ch (stereo)

0010b: 3ch
 0011b: 4ch
 0100b: 5ch
 0101b: 6ch
 0110b: 7ch
 0111b: 8ch

(multichannel)

Note 10: "dynamic_range_control" describes the dynamic word control word to compress the dynamic range from the first access unit.

The packet data structure of the linear PCM audio and corresponding frame size of 48KHz/192KHz are as shown in Table 17.

Table 17

Stream Mode			Data in a Packet			
Number of Channels	fs (KHz)	Quantization	Maximum number of samples in a packet	Data size (byte)	Packet Stuffing of first/other PES packet (byte)	Padding packet for first/ other other PES packet (byte)
1 mono	48/96/192	16	1004	2008	2/5	0/0
	48/96/192	20	804	2010	0/3	0/0
	48/96/192	24	670	2010	0/3	0/0
2 stereo	48/96/192	16	502	2008	2/5	0/0
	48/96/192	20	402	2010	0/5	0/0
	48/96/192	24	334	2004	6/0	0/9
3	48/96/192	16	334	2004	6/0	0/9
	48/96	20	268	2010	0/3	0/0
	48/96	24	222	1988	0/0	12/15
4	48/96	16	250	2000	0/0	10/13
	48/96	20	200	2000	0/0	10/13
	48/96	24	166	1992	0/0	18/21
5	48/96	16	200	2000	0/0	10/13
	48/96	20	160	2000	0/0	10/13
	48	24	134	2010	0/3	0/0
6	48/96	16	166	1992	0/0	18/21
	48	20	134	2010	0/3	0/0
	48	24	110	1980	0/0	30/33
7	48	16	142	1988	0/0	22/25
	48	20	114	1995	0/0	15/18
	48	24	94	1974	0/0	36/39

Table 17 (continued)

Stream Mode			Data in a Packet			
Number of Channels	fs (KHz)	Quantization	Maximum number of samples in a packet	Data size (byte)	Packet Stuffing of first/other PES packet (byte)	Padding packet for first/ other other PES packet (byte)
8	48	16	124	1984	0/0	26/29
	48	20	100	2000	0/0	10/13
	48	24	82	1968	0/0	42/45
9	48	16	110	1980	0/0	30/33
	48	20	88	1980	0/0	30/33
10	48	16	100	2000	0/0	10/13
	48	20	80	2000	0/0	10/13
11	48	16	90	1980	0/0	30/33
12	48	16	82	1968	0/0	42/45
13	48	16	76	1976	0/0	34/37

If the number of samples is less than in Table 17, the length of padding packet may increase to adjust the pack size. Samples shall be aligned at the packet boundary. Namely, the audio sample data of every audio packet starts with the first byte of S_{2n} . The number of the audio samples in a packet always becomes even.

Thus, in DVD-Audio format, the linear PCM data is processed in frames and GOF. The DVD-Audio may use the sampling frequency of 192KHz, whereby the basic rule of linear PCM coding may be set as shown in Table 18.

Table 18

Sampling frequency(fs)	48KHz/44.1KHz	96KHz/88.2KHz	192KHz/176.4KHz
Sampling Phase	Shall be simultaneous for all channels in all streams		
Quantization	16 bits or more, 2's complementary code		
Emphasis	Can be applied (zero point: 50 μ s, pole: 15 μ s)	cannot be applied	

One audio frame contains 320 audio sample data when fs is 192KHz. One GOF corresponds to the presentation time of 1/30 second as in the DVD-Video. The sampling frequency of 96KHz is used to achieve multichannel to store quality audio data.

When recording the linear PCM audio data using the sampling frequency of 48KHz and quantization of 16bits, 13 channels are available so as to record the audio data of 10 channels required by the present multichannel music. However, when using the sampling frequency of 192KHz and quantization of 24bits, only 2 channels are available to record audio data, which can not meet the requirement of the multichannel music. Namely, it is impossible to achieve multichannel audio function with high sampling frequency and a great number of data bits. However, such limitation may be resolved by lossless coding or pseudo-lossless coding. The compression ratio of lossless coding is about 2:1 while that of pseudo-lossless psychoacoustic coding is about 4:1.

It is assumed that the inventive DVD-Audio employs DTS (Digital Theater System) coding which is pseudo-lossless psychoacoustic coding with the compression ratio of about 4:1. Further, the DTS makes it possible to perform lossless coding. The DTS can provide a sufficient number of channels without significant degradation of sound quality. For the DTS may carry out coding for a high specification with the sampling frequency of 192KHz and 24bit quantization compared to different compression coding algorithms presently proposed, and has been developed to minimize degradation of sound quality instead of reducing the bit rate. The DTS has the sampling frequencies of 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz or 176.4KHz, the quantization bit number of 16, 20 and 24, and the number of channels from 1ch coding to the maximum allowed by the bit rate. The number of audio channels may be determined by Eq. 2.

EP 0 867 877 A2

$$\text{Eq. 2} \quad N = \frac{Mby * Ccy}{Fs * Qb}$$

Fs: Sampling Frequency(Hz) → 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz or 176.4KHz

Qb: Number of Quantization Bits → 16, 20, or 24

Mby: Maximum Data Transfer Rate of DVD(Mbps) → 10.08Mbps

Ccy: Compression ratio of Pseudo-Lossless Psychoacoustic Coding

N: Maximum Number of Audio Channels Determined by Data Transfer Rate, Sampling Frequency and Number of Quantization Bits of DVD

Assuming the DTS coding with the compression ratio of 4:1 is used for compression coding, the number of channels determined by Eq. 2 is as shown in Table 19. Therefore, in accordance with Eq. 2, each sampling frequency can support 8 or more channels.

Table 19

Sampling Frequency	Number of Quantization Bits	Maximum Number of Channels
48KHz/44.1KHz	16 bits	52
48KHz/44.1KHz	20	42
48KHz/44.1KHz	24	35
96KHz/88.2KHz	16	26
96KHz/88.2KHz	20	21
96KHz/88.2KHz	24	17
192KHz/176.4KHz	16	13
192KHz/176.4KHz	20	10
192KHz/176.4KHz	24	8

Thus, the inventive DVD-Audio is constructed based on the structure of the MPEG2 system layer, and therefore, the compression coded audio pack structure comprises a pack header of 14 bytes and compression coded audio packets each having at maximum 2021 bytes, as shown in Figure 26. The pack header meets the specification of MPEG2 system layer.

The structure of the compression coded audio packet is also based on the specification of MPEG2 system layer. The compression coded audio packet is constructed as shown in Tables 20 and 21. The Table 20 has the same structure as Table 10 presenting the structure of linear PCM audio packet of the DVD-Video.

Table 20

Field	Bit	Byte	Value	Comment
packet_start_code_prefix	24	3	00 0001h	
stream_id	8	1	1011 1101b	private_stream_1
PES_packet_length	16	2		
'10'	2	3		
PES_scrambling_control	2	3	00b	not scrambled
PES_priority	1	3	0	no priority
data_alignment_indicator	1	3	0	not defined by descriptor
copyright	1	3	0	not defined by descriptor
original_or_copy	1	3	1 or 0	original:1 copy:0
PTS_DTS_flags	2	3	10 or 00b	
ESCR_flag	1	3	0	no ESCR field

Table 20 (continued)

Field	Bit	Byte	Value	Comment
ES_rate_flag	1	3	0	no EST rate field
DSTM_trick_mode_flag	1	3	0	no trick mode field
additional_copy_info_flag	1	3	0	no copy info field
PES_CRC_flag	1	3	0	no CRC field
PES_extension_flag	1	3	0 or 1	
PES_header_data_length	8	3	0 to 15	
'0010'	4	5	provider defined	Note 1
PTS[32...30]	3	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[29...15]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PTS[14...0]	15	5	provider defined	Note Note 1
marker_bit	1	5	provider defined	Note 1
PES_private_data_flag	1	1	0	Note 2
pack_header_field_flag	1	1	0	Note 2
program_packet_sequence_counter_flag	1	1	0	Note 2
P_STD_buffer_flag	1	1	1	Note 2
reserved	3	1	111b	Note 2
PES_extension_flag_2	1	1	0	Note 2
'01'	2	2	01b	Note 2
P_STD_buffer_scale	1	2	1	Note 2
P_STD_buffer_size	13	2	58	Note 2
stuffing_byte	-	0-7		

Table 21

Field	Bit	Byte	Value	Comment
sub_stream_id	8	1	#### &***b	Note 1
number_of_frame_headers	8	1	Provider Defined	Note 2
first_access_unit_pointer	16	2	Provider Defined	Note 3
DTS Audio data area				

In Table 21, Notes 1 to 3 are described as follows:

Note 1: "sub_stream_id" varies with the compression coding system, and so becomes "1000 1***b" with the DTS. "****" represents decoding the audio data stream number.

Note 2: "number_of_frame_headers" describes the number of audio frames whose first byte is in this audio packet.

Note 3: The access unit is the audio frame. The first_access_unit is the first audio frame which has the first byte of the audio frame.

Thus, the DVD-Audio is provided with more than 8 channels to perform the compression coding, available sampling frequencies of 48KHz, 44.1KHz, 96KHz 88.2KHz, 192KHz or 176.4KHz, quantization bit number of 16, 20 and 24, compression ratio from 1:1 to over 5:1, down mixing, dynamic range control and time stamp.

The DTS compression algorithm used in the present embodiment has a compression ratio low enough to provide significantly improved sound quality, and may optionally be employed in DVD-Video. The DVD-Video has the structures of DTS pack and packet and restricted items for DTS. For the restricted items, the bit rate after compression is limited up to 1.5Mbps and the sampling frequency for compressible data is only 48KHz. However, in the inventive DVD-Audio employing the DTS algorithm, the sampling frequency is extended to 192KHz, quantization bit number to 24bits, multichannel data compressed to about 4:1, thereby providing desirable sound quality. Namely, the compression coding used in the inventive DVD-Audio employs sampling frequencies of 48KHz/44.1KHz/96KHz/88.2KHz/192KHz/176.4KHz and quantization bit number of 16bits/20bits/24bits so as to compress multichannel linear PCM data by about 4:1 without degrading sound quality.

The DVD-Audio may additionally include VIDEO_TS and VMG for the information region in a structure which is the same as in the DVD-Video in order to have compatibility with a DVD-Video player. However, the DVD-Video restricts the data transfer rate of an audio stream within 6.144Mbps, as shown in Table 11.

Table 22

	Transfer Rate		Note
	Total Streams	One Stream	
VOB	10.08 Mbps	-	
Video Streams	9.80 Mbps	9.80 Mbps	Number of Streams=1
Audio Streams	9.80 Mbps	6.144 Mbps	Number of Streams=8(max)
Sub-picture Streams	9.80 Mbps	3.36 Mbps	Number of Streams=32(max)

Hence, the DVD-Video player may reproduce only the data satisfying the DVD-Video specification among the audio data of the DVD-Audio. The linear PCM data reproduced by the DVD-Video player is as shown in Table 7. Of course, compression coded DTS data is played by the DVD-Video player to reproduce only DTS streams specified by the DVD-Video. For example, it is assumed that the titles to be stored into a DVD are as shown in Table 23.

Table 23

Sampling Frequency	Number of Quantization Bits	Number of Channels	Remark
48KHz	16	8ch	Title 1
96KHz	16	4ch	Title 2
96KHz	24	2ch	Title 3
96KHz	24	4ch	Title 4
196KHz	24	2ch	Title 5

Then, the VIDEO_TS and VMG are recorded with the attribute and position information of Titles 1 to 3 but not with the information of Titles 4 and 5. On the contrary, the AUDIO_TS and AMG of the DVD-Audio are recorded with the information of all the Titles 1 to 5 because the Titles 1 to 3 meet the specifications of both DVD-Video and DVD-Audio but the Titles 4 and 5 only meet the specification of the DVD-Audio. Hence, the Titles 4 and 5 may be played only by the DVD-Audio player. If there is an available space in the data zone, the Titles 4 and 5 may be separately recorded in the available data space with the sampling frequency, quantization bit number and channel number reduced, and the information on the Titles 4 and 5 are stored into the VIDEO_TS and VMG. Then, the Titles 4 and 5 may be reproduced by a DVD-Video player.

If the compression coding DTS does not meet the specification of the DVD-Video concerning data transfer rate, number of channels, sampling frequency of original data, quantization bit number, etc., the information is recorded only in the AUDIO_TS and AMG but not in the VIDEO_TS and VMG. Namely, only the DTS streams satisfying the specification of the DVD-Video may be recorded in the VIDEO_TS and VMG. In order to reproduce the DTS streams not conforming to the specification of the DVD-Video, they must be coded to meet the transfer rate, number of channels, sampling frequency and quantization bit number specified for the DVD-Video, stored to be recorded in the VIDEO_TS and VMG.

The AMG and ATSI_MAT of the DVD-Audio has the same structure as the VMG and VTSI of the DVD-Video. However, the audio data exceeding the specification of the DVD-Video such as sampling frequency of 192KHz and 8 or more channels must be changed to be reproduced by the DVD-Video player. Hence, the disk is made as follows:

When the content of a title to be recorded on the disk is within the specification of the DVD-Video, any one of the VMG and the AMG is kept to make the VIDEO_TS and AUDIO_TS direct the file through the VMG or AMG. Then, the DVD-Audio player regards the file as AMG to play while the DVD-Video player regards the file as VMG to play.

Meanwhile, if any of the titles to be recorded in the disk has an audio stream which does not meet the specification of the DVD-Video, both the VMG and the AMG are kept together, and the VMG is not recorded with the information on the titles which do not conform to the specifications of the DVD-Video. Of course, the AMG has not recorded with the information on the titles which have the sampling frequency, number of quantization bits and number of channels altered to be compatible with the DVD-Video player.

However, when the AMG and ATSI_MAT of the DVD-Audio are structured entirely different from the VMG and VTSI_MAT of the DVD-Video, both VMG and AMG must be prepared, and thus both VTSI_MAT and ATSI_MAT. Of course, the VMG and VTSI_MAT are provided with the information on the audio titles conforming to the specification of the DVD-Video.

The apparatus for playing the DVD-Audio may be designed independently from the DVD-Video player, but the inventive DVD-Audio player may be combined with the DVD-Video player.

Referring to Figure 27 for illustrating the structure of a DVD-Audio player, a system controller 111 controls the whole operation of the DVD-Audio player, serving the user interface. The system controller 111 determines whether the inserted disk is a DVD-Video or DVD-Audio by checking effective data included in the VIDEO_TS and AUDIO_TS directory. When it is checked that effective data exists from the AUDIO_TS directory, the system controller 111 determines the inserted disk to be a DVD-Audio and thus, controls its playing operation. But if it is determined that no effective data exists from the AUDIO_TS, the system controller 111 determines the inserted disk to be a DVD-Video, and thus, stops the playing operation.

A pickup device 112 is provided to read the data stored in the DVD-Audio. A servo controller 113 controls the pickup device 112 to perform various servo functions under the control of the system controller 111. A data receiver 114 analyzes and corrects an error occurring in the data output from the pickup device 112, and includes an error correction circuit. An audio decoder 115 transfers the audio information from the data receiver 114 to the system controller 111, decoding received audio data under the control of the system controller 111.

The audio decoder 115 is designed to decode the linear PCM audio data and compression coded audio data according to the present invention, as shown in Figure 28. Referring to Figure 28, an input data buffer 211 stores the audio data output from the data receiver 114. A stream selector 212 selectively outputs the audio data stream from the input buffer 211 under the control of the system controller 111. A linear PCM decoder 213 decodes linear PCM audio data received from the stream selector 212 to the original audio data. A coding data decoder (Pseudo-Lossless Psychoacoustic Decoding Circuit) 214 decodes compression coded data from the stream selector 212 to the original audio data. An output buffer 215 stores the audio data delivered by the decoding parts 213 and 214. A digital audio formatter 216 converts the audio data from the decoding parts 213 and 214 into a format specified by the system controller 111. The timing controller 210 generates timing control signals to control the operations of the parts of the audio decoder 115 under the control of the system controller 111.

A digital processor (High-bit High-sampling Digital Filter) 116 filters audio data from the audio decoder 115 under the control of the system controller 111. An audio output circuit (High Performance Digital to Analog Converters and Analog Audio Circuitry) 117 converts the audio data from the digital processor 116 into an analog signal.

Referring to Figures 27 and 28, the data receiver 114 transfers the audio data reproduced from a DVD-Audio through the pickup device 112 to the audio decoder 115. The reproduced audio data are sequentially stored into the input buffer 211 of the audio decoder 115. The audio data stored in the input buffer 211 are selected by the stream selector 212 and transferred to the decoding parts 213 and 214. Namely, when the system controller 111 demands decoding of the linear PCM audio data, the stream selector 212 transfers the audio data stored in the input buffer 211 to the linear PCM decoder. In addition, when the system controller 111 demands decoding of the compression coded data, the stream selector 212 transfers the audio data stored in the input buffer to the coding data decoder 214.

Describing the decoding operation of the linear PCM audio data, the linear PCM decoder 213 generally performs multichannel downmixing, sampling frequency conversion and requantization of the input signal. For example, when 8-channel data produced from the stream selector 212 is required to be converted into 2-channel data, the linear PCM decoder 213 performs multichannel downmixing to produce an output of the required channel number. Further, when the input data sampled at 192KHz is required by the system controller 111 to be converted into data sampled at 96KHz, the linear PCM decoder 213 performs the sampling frequency conversion to produce audio data of the required sampling frequency. In addition, when the input audio data of 24 bit quantization is required by the system controller 111 to be converted into data of 16 bit quantization, the linear PCM decoder 213 performs the requantization process to produce audio data of the required number of bits.

Describing the decoding operation of the compression coded audio data, the coding data decoder 214 decodes the compression coded audio data by carrying out the corresponding algorithm under the control of the system controller 111. In this case, the form of the audio data produced from the coding data decoder 214 is specified by the system controller 111. In the present embodiment, the coding data decoder 214 may be a DTS decoder. In addition, the coding data decoder 214 also carries out the multichannel downmixing, sampling frequency conversion and requantization of the input signal together with the algorithm decoding.

The audio data decoded by the decoding parts 213 and 214 is transferred to the output buffer 215 and digital audio formatter 216. The output buffer 215 stores the decoding audio data to synchronize with a control signal supplied by the timing controller 210. The digital audio formatter 216 adjusts the decoded audio data to the transmission format between the digital devices, synchronizing it with a control signal from the timing controller 210. In this case, the output audio data may be delivered to an audio/video system or a computer having the same transmission format.

The decoded audio data from the audio decoder 115 is processed through the digital processor 116 and converted by the audio output circuit 117 into an analog signal. The digital processor 116 comprises a plurality of digital filters to eliminate noises outside the audio signal band. The digital processor 116 requires a filter coefficient having a much higher resolution and number of taps than the digital filters used in the conventional DVD or CD to process the audio data sampled at 192KHz and quantized by 24 bits. Of course, when a D/A converter of 96KHz and 192KHz becomes commonly available, the digital processor 116 may be included in the D/A converter. The audio output circuit 117 includes a plurality of D/A converters to convert the audio data deprived of noises into an analog audio signal.

Referring to Figure 29 for illustrating an apparatus for playing both DVD-Video and DVD-Audio, the system controller 311 controls the whole operation of the DVD-Audio/Video player, serving the user interface. The system controller 311 determines whether the inserted disk is a DVD-Video or DVD-Audio by checking effective data included in the VIDEO_TS and AUDIO_TS directory. When there is effective data from the AUDIO_TS directory, the system controller 311 determines the inserted disk to be a DVD-Audio and thus, controls its playing operation. But if there is no effective data from the AUDIO_TS, the system controller 311 determines the inserted disk to be a DVD-Video, stops the present DVD-Audio playback mode, and changes to the playback mode of the DVD-Video.

A pickup device 312 is provided to read the data stored in the DVD-Audio. A servo controller 313 controls the pickup device 312 to perform various servo functions under the control of the system controller 311. A data receiver 314 analyzes and corrects an error occurring in the data output from the pickup device 312, and includes an error correction circuit. An audio/video decoder 315 transfers the audio information from the data receiver 314 to the system controller 311, decoding received audio data under the control of the system controller 311.

The audio/video decoder 315 is designed to decode video data and audio data, as shown in Figure 30. Referring to Figure 30, an input data buffer 411 stores the audio and video data output from the data receiver 314. A stream parser 412 selectively outputs the audio and video data stream from the input buffer 411 under the control of the system controller 311. An audio decoding circuit 413 decodes the audio data selected by the stream parser 412 in response to a control data from the system controller 311. A decoding audio output circuit 414 outputs the decoded audio data from the audio decoding circuit 413. A video decoding circuit 415 decodes the video data selected by the stream parser 412 in response to a control signal of the system controller 311. A decoding video output circuit 416 outputs the decoded video data from the video decoding circuit 415. A timing controller 410 generates timing control signals to control the operations of the parts of the audio/video decoder 315 under the control of the system controller 311.

The audio decoding circuit 413 must be provided with decoding elements corresponding to a linear PCM system, an MPEG system, an AC-3 system and a compression coding system. The linear PCM system and compression coding system require additional elements to reproduce the audio data recorded in the inventive DVD-Audio. Namely, the decoding elements are provided to reproduce the audio data formed by sampling frequency, quantization bits and audio channels according to the present invention. Also provided is a stream selector to distribute the audio data corresponding to the decoding elements.

A digital processor (High-bit High-sampling Digital Filter) 316 filters audio data from the audio/video decoder 315 under the control of the system controller 311. An audio output circuit (High Performance Digital to Analog Converters and Analog Audio Circuitry) 117 converts the audio data from the digital processor 316 into an analog signal. A video output circuit (NTSC Encoder Video Digital to Analog Converter's Analog Video Circuitry) 318 encodes video data from the audio/video decoder 315 in NTSC, converting the video data into an analog video signal.

Referring to Figures 29 and 30, the data reproduced from the disk through the pickup device 312 is transferred to the data receiver 314 to analyze it and correct an error in it, and is applied to the audio/video decoder 315. The data produced from the data receiver 314 is applied to the input buffer 411 of the audio/video decoder 315. The stream parser 412 selects a required stream according to a control data of the system controller 311, and analyzes the stream to deliver the video data to the video decoding circuit 415 and the audio data to the audio decoding circuit 413.

The audio decoding circuit 413 transforms the audio data from the stream parser 412 according to the requirements of the system controller 311. The audio decoding circuit 413 must include the decoding functions to decode audio data of both DVD-Video and DVD-Audio. The video decoding circuit 415 decodes and transforms the input video data. The

video data transformation means sub_title process, pan_scan, etc.

The decoded audio and video data are respectively transferred to the decoding audio and video output circuits 414 and 416, and are finally transmitted outside in synchronism with timing control signals of the timing controller 410. The decoding audio output circuit 414 adjusts the decoded audio data to the transmission format between the digital devices. The audio data generated from the decoding audio output circuit 414 is transferred to a different audio/video system or computer.

As shown in Figure 29, the audio/video decoder 315 follows the specification of the DVD-Video when processing video signals, and carries out both the inventive algorithm and the audio decoding algorithm according to the specification of the DVD-Video. Thus, the audio decoding circuit 413 contains the linear PCM and DTS algorithms of the audio specification of the DVD-Video, and therefore both DVD-Video and DVD-Audio may be reproduced.

In this case, the algorithm required for the audio decoding of the DVD-Video indicates linear PCM decoding(1) + AC-3 decoding + MPEG decoding while the algorithm required for the audio decoding of the DVD-Audio indicates linear PCM decoding(2) + coding data decoding (Pseudo-Lossless Psychoacoustic Decoding). Hence, the linear PCM algorithm in the DVD-Video is included in the linear PCM algorithm according to the present invention. The decoding algorithm employed in the DVD-Video and DVD-Audio includes the functions as expressed by Eq. 3, carried out by the audio decoding circuit

Eq. 3 Audio Decoder = Linear PCM Decoder(2) + Pseudo-

Lossless Psychoacoustic Decoder + AC-3 Decoder + MPEG

Decoder.

Thus, such an apparatus for playing both DVD-Video and DVD-Audio detects the VIDEO_TS and AUDIO_TS of the inserted DVD to set the audio decoding mode. The audio data of the DVD-Audio with the video data eliminated is shown in Table 24.

Table 24

Sampling Frequency	Number of Quantization Bits	Bit Rate per Channel	Number of Channels	Required Data Capacity
48KHz	16bits	768Kbps	8ch	5.99Gbyte
	20bits	960Kbps	8ch	5.76Gbyte
	24bits	1.152Mbps	8ch	5.53Gbyte
96KHz	16bits	1.536Mbps	6ch	5.53Gbyte
	20bits	1.920Mbps	5ch	5.76Gbyte
	24bits	2.304Mbps	4ch	5.53Gbyte

The compression coding system specified in the DVD-Video may compress data at a maximum of 448Kbps. The sampling frequency to allow compression is 48KHz, and the number of quantization bits to allow compression is 16bits. Hence, the amount of data to be handled is limited, and the compression ratio is about 10:1. Therefore, it is unsuitable for audio data, especially in view of sound quality. If the compression algorithm is a dolby AC-3 algorithm, the quantization system is 16 bit linear PCM, the sampling frequency is 48KHz, the maximum number of channels to record at is a maximum of 6ch (one of the audio channels having a subwoofer channel containing audio data below 200Hz and using .1 of that channel), and possible bit rate is 192Kbps-448Kbps. The dolby AC-3 algorithm is very limited in the number of quantization bits, the sampling frequency, and the high compression ratio, resulting in serious degradation of sound quality and is thus unsuitable for audio use exclusively. In addition, when the compression algorithm is MPEG2 algorithm, the quantization system is 16 bits-24 bits linear PCM, the sampling frequency is 48KHz, the maximum number of channels to record is 8ch (one of the audio channels having a subwoofer channel containing audio data below 200Hz and using .1 of that channel), and the possible bit rate is 64Kbps-912Kbps. This algorithm has a high quantization bit number for possible coding and a high channel number to record, but the sampling frequency is limited and the compression ratio high, thereby causing degradation of sound quality.

However, assuming that the transfer rate is 10.08Mbps and the time for reproducing is 80 minutes for the DVD-Audio, the linear PCM audio is achieved as shown in Table 25. Furthermore, even in the case that the sampling frequency is 44.1KHz, 88.2KHz and 176.4KHz, the PCM audio may have similar values as those shown in Table 25.

Table 25

Sampling Frequency	Number of Quantization Bits	Bit Rate per Channel	Number of Channels	Required Data Capacity
48KHz	16bits	768Kbps	13ch	5.99Gbyte
48KHz	20bits	960Kbps	10ch	5.76Gbyte
	24bits	1.152Mbps	8ch	5.53Gbyte
96KHz	16bits	1.536Mbps	6ch	5.53Gbyte
	20bits	1.920Mbps	5ch	5.76Gbyte
	24bits	2.304Mbps	4ch	5.53Gbyte
192KHz	16bits	3.072Mbps	3ch	5.53Gbyte
	20bits	3.840Mbps	2ch	4.61Gbyte
	24bits	4.608Mbps	2ch	5.53Gbyte

Employing DTS in the compression coding system, the quantization uses 16bit, 20bit or 24bit linear PCM, a sampling frequency of 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz or 176.4KHz, the maximum number of channels to record is 13ch, and the compression ratio is about 4:1. The DTS compression coding has a high quantization bit number and sampling frequency with a reduced compression ratio, keeping high sound quality.

As described above with reference to Figures 27 and 29, the audio or audio/video player determines the kind of DVD by checking if effective data is stored in the AUDIO_TS directory. Namely, the DVD-Audio player performs the reproducing function or not according to whether is effective data stored in the AUDIO_TS directory. The audio/video player as shown in Figure 29 performs the audio or video playing function according to whether effective data stored in the AUDIO_TS directory.

Figure 31 describes the operation of the inventive concept with reference to the audio/video player as shown in Figure 29. An inserted DVD is checked by the system controller 311 in steps 511, and the content of the AUDIO_TS directory is read in step 513. In step 515, it is checked whether there is effective data stored in the AUDIO_TS directory. If the inserted DVD is a DVD-Video, there is no effective data in the AUDIO_TS directory. Namely, the DVD-Video has the AUDIO_TS directory, but it is empty. However, if the inserted DVD is a DVD-Audio, the AUDIO_TS directory contains the information on the positions of the audio data as shown in Figures 10 to 18C.

Detecting effective data in the AUDIO_TS directory in step 515, the system controller 311 determines the inserted disk as being a DVD-Audio in step 517. In step 519, the position of the AMG as shown in Figures 10 and 11 is located by reading the AUDIO_TS directory. Then, the pickup device 312 is moved to the position of the AMG in the DVD in step 521, where the AMG is read to confirm the information on the places storing the entire audio data. As shown in Figures 10 and 11, the AMG contains the information on all audio titles stored in the DVD-Audio as well as the attribute and position information of each title.

In step 523, the system controller 311 checks whether there is a demand for reproducing a specific audio title. The demand is made by the user or a command stored in the DVD-Audio. Detecting the demand to reproduce a title, the system controller 311 locates the position of the title in the disk according to the position information obtained from the AMG in step 525, and in step 527, moves the pickup device 312 to the position of the ATSI_MAT of the title to read it. In step 529, the information of the ATSI_MAT as shown in Figures 15 to 18C is analyzed to determine the reproducing algorithm by discovering the kind and attribute of the audio title to play. In step 531, the audio decoding circuit 413 of the audio/video decoder 315 is set to the selected audio data from the DVD-Audio according to the reproducing algorithm. The information required to set the audio decoding circuit 413 are the audio coding mode, the sampling frequency, the quantization bit number and the channel number. Finally, the selected title is decoded by the audio decoding circuit 413 played in step 533.

On the other hand, if there is no effective data in the AUDIO_TS directory in step 515, the system controller 311 determines the inserted disk as being a DVD-Video, and in step 537, the position of the VMG is located by reading the VIDEO_TS directory. Then, the pickup device 312 is moved to the position of the VMG in the DVD in step 539, where the VMG is read to confirm the information on the places storing the entire video data. Thereafter, if there is a demand to reproduce a title, the video, sub-picture and audio data of the selected title are played according to the information stored in the VTSI_MAT.

Likewise, a DVD-Audio player, which only reproduces data from a DVD-Audio, also performs the steps 511 to 533 for the DVD-Audio, but stops the playing operation for a DVD-Video.

After setting the audio decoding circuit 413 according to the information stored in the ATSI_MAT, the system controller 311 analyzes the audio pack stored in the data area of a DVD-Audio from step 533 going through the steps as shown in Figure 32.

In step 611, the system controller 311 commands a decoding operation of the audio decoding circuit 413, and in step 613, controls the stream parser 412 to transfer the received audio data to the audio decoding circuit 413 provided with the corresponding audio algorithm. Then, the audio decoding circuit 413 decodes the received audio data according to the algorithm set by the system controller 311. Here, the system controller 311 checks the operational state of the audio decoding circuit 413 in step 615. Detecting an abnormal state of the audio decoding circuit, the process proceeds to step 621 to control the decoding circuit 413 to stop the decoding operation, and the stream parser 412 is controlled to stop transferring data. Then, after performing the repair algorithm according to the abnormal state, the process is returned to step 611.

However, if the audio decoding circuit 413 performs the decoding operation normally in step 615, the decoded audio data is output through the decoding audio output circuit 414 in step 617. Thereafter, the operational state of the audio decoding circuit 413 is checked again in step 619. Detecting the abnormal state, the process proceeds to the step 621, or otherwise the process is returned to decode the next audio data. When the audio stream is fully decoded by the audio decoding circuit 413, the system controller 311 controls the digital processor 316 and audio output circuit 317 to convert the decoded audio data into an analog signal.

Thus, the inventive DVD includes a VIDEO_TS and AUDIO_TS directory to make it possible to distinguish a DVD-Audio from a DVD-Video by checking effective data stored in the AUDIO_TS directory. The DVD-Audio may be recorded with the audio data sampled at a maximum of 192KHz and quantized by 24bits. Further, audio channels may be extended greatly. Therefore, by reproducing the audio data in the DVD audio, it is possible to reproduce an audio signal of high quality which is suitable for multi-channel music. The number of channels limited by the data transfer speed, the sampling frequency and the quantization bit number is extended by using a coding algorithm.

In the case where the linear PCM data sampled at the sampling frequency of 192KHz is divided into the linear PCM data of 96KHz and the data of 192KHz so that the data of 96KHz is recorded by the lossless psychoacoustic coding, the DVD of the present invention records the audio titles at the sampling frequency of 192KHz in the AUDIO_TS directory by linear PCM lossless coding, and records the video titles at the sampling frequency of 96KHz in the VIDEO_TS directory by linear PCM coding. The DVD-audio player reads the AUDIO_TS to demodulate the data by the lossless psychoacoustic coding, and mixes it with the data of 96KHz to reproduce it into the data of 192KHz. The DVD-video player reads the VIDEO_TS directory to reproduce the data of 96KHz. That is, by recording one title into the AUDIO_TS and VIDEO_TS separately, the DVD-audio player may reproduce the data at 192KHz and the DVD-video player may reproduce the data at 96KHz.

Furthermore, in the case where the music data sampled at 44.1KHz for an existing CD is provided to the DVD, the music data of 44.1KHz should be converted into the music data of 48KHz in order to provide it by using the conventional DVD-video format. Undesirably, however, the audio data may be degraded during the conversion. The DVD according to embodiments of the present invention can support the audio frequency sampled at 44.1KHz in DVD-audio format. Thus, it is possible to record the audio data as it is without conversion of the sampling frequency and provide it together with the video data, thereby providing audio sound of high quality.

Preferably, a general DVD-video player should be connected to the DVD-audio player which can reproduce the 24-bit data of 192KHz, since the general DVD-video has a specification inferior to that of the DVD-audio.

The reader's attention is directed to all papers and documents which are filed concurrently with or previous to this specification in connection with this application and which are open to public inspection with this specification, and the contents of all such papers and documents are incorporated herein by reference.

All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive.

Each feature disclosed in this specification (including any accompanying claims, abstract and drawings), may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features.

The invention is not restricted to the details of the foregoing embodiment(s). The invention extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

Claims

1. A DVD-Audio disk comprising:

5 a data zone to store data to be reproduced; and

an information zone to store information on said data to be reproduced;

10 wherein said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), said AUDIO_TS directory including information on an audio manager (AMG) having information on audio titles; and

15 wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second or third sampling frequency corresponding to the data to be reproduced and de-
coding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute.

20 2. A DVD-Audio disk as claimed in Claim 1, wherein if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16bits, 20bits and 24bits, said first to third sampling frequencies are respectively 48KHz, 96KHz and 192KHz, and a maximum number of said audio channels is 8.

25 3. A DVD-Audio disk as claimed in Claim 1, wherein if said audio coding mode is a compression coding system, said first to third quantization bit numbers of the audio data before compressing are respectively 16bits, 20bits and 24bits, said first to third sampling frequencies are respectively 48KHz, 96KHz and 192KHz, and a maximum number of said audio channels is 8.

30 4. A DVD-Audio disk as claimed in Claim 1, 2 or 3, wherein said VIDEO_TS directory includes information on a position of a video manager (VMG) having information on positions of said audio titles reproducible by a DVD-Video player, said VMG being recorded with the information on said audio titles, and each of said audio titles including video title set information and a plurality of contiguous video objects (VOBs).

35 5. An apparatus for playing a DVD-Audio disk, wherein the DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute, said apparatus comprising:

a data receiver to receive said audio data retrieved from the DVD-Audio disk;

50 a controller to generate an audio control signal including said audio coding mode, the one of said first through sixth sampling frequencies, the number of audio channels, and one of said first through third quantization bit numbers based upon information on said audio data if said Audio_TS has effective data, and, stopping a playing operation of said apparatus if said Audio_TS does not have effective data;

55 an audio decoder to decode said audio data, to multi-channel mix, sampling-frequency convert and requantize said decoded audio signal according to said audio control signal, to generate output decoded audio data; and

an audio output circuit to convert said output decoded audio data into an analog audio signal.

6. An apparatus as claimed in Claim 5, wherein said audio decoder further comprises:

a stream selector to select one of a plurality of audio streams which form said audio data according to said audio coding mode;

a linear PCM decoding circuit to decode said selected audio stream if said selected audio stream is a linear PCM audio stream, and to sample frequency convert, multichannel downmix and requantize said decoded audio data according to said audio control signal; and

a coding data decoding circuit to decode said selected audio stream if said selected audio stream is a compression coded audio stream using a corresponding extension algorithm, and to sample frequency convert, multichannel downmix and requantize said decoded audio data according to said audio control signal.

7. An apparatus for playing a DVD-Audio disk and a DVD-Video disk, wherein said DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced, and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute, said DVD-Video disk including a data zone to store video data, said apparatus comprising:

a data receiver to receive said audio data retrieved from said DVD-Audio disk when said DVD-Audio disk is loaded in said apparatus for reproduction, and to receive said video data retrieved from said DVD-Video when said DVD-Video disk is loaded in said apparatus for reproduction;

a controller to generate an audio control signal including said audio coding mode, the one of said first through sixth sampling frequencies, the number of audio channels, and one of said first through third quantization bit numbers based upon information on said audio data if said Audio_TS has said effective data, and stopping a playing operation of said apparatus if said Audio_TS does not have said effective data;

a stream parser to separate said video data and audio data output from said data receiver according to a mode control signal from said controller;

a video decoding circuit to decode said video data output from said stream parser in response to said controller controlling a DVD-Video playing mode of said apparatus;

a video output circuit to encode said video data output from said video decoding circuit in NTSC, and to convert said encoded video data into an analog video signal;

an audio decoder having a plurality of audio decoding circuits to decode said audio data output from said stream parser by selecting a corresponding decoding circuit according to said audio coding mode, and to multi-channel mix, sampling-frequency convert and requantize said decoded audio signal according to said audio control signal, to generate an output decoded audio signal; and

an audio output circuit to convert said output decoded audio signal into an analog audio signal.

8. An apparatus as defined in Claim 7, wherein said audio decoder further comprises:

a stream selector to select one of a plurality of audio streams which form said audio data according to said audio coding mode control signal to deliver said selected audio stream to the corresponding one of said plurality of audio decoding circuits;

said plurality of audio decoding circuits including a linear pulse code modulated (PCM) decoding circuit to

decode said selected audio stream when said selected audio stream is a linear PCM audio stream, and to sampling frequency convert, multichannel downmix and requantize said decoded linear PCM audio stream according to said audio control signal, and

5 a coding data decoding circuit to decode said selected audio stream when said selected audio stream is a compression coded audio stream by a corresponding extension algorithm, and to sampling frequency convert, multichannel downmix and requantize said decoded compression coded audio stream according to said audio control signal.

10 9. A method for playing a DVD-Audio disk, wherein the DVD-Audio disk includes a data zone to store data to be reproduced by the apparatus and an information zone to store information on said data to be reproduced, said information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles, wherein said data zone includes said audio titles each having audio title set information (ATSI) followed by a
15 plurality of contiguous audio objects (AOBs), said ATSI includes a plurality of audio stream attributes each having an audio coding mode, a first, second or third quantization bit number corresponding to the data to be reproduced, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the data to be reproduced, and decoding algorithm information relating to a number of audio channels of the data to be reproduced, and each of said AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm
20 stored in the audio stream attribute, said method comprising the steps of:

locating the AMG when the AUDIO_TS directory includes effective data;

checking out other information of said DVD-Audio disk from the information of the AMG;

25 reading position data of one of said audio titles selected according to position information of the AMG upon receiving a command for reproducing said one of said audio titles; and

30 setting an audio decoder to carry out an algorithm for reproducing said one of said audio titles by reading the audio stream attribute of the corresponding ATSI-MAT.

10. A DVD-Audio disk comprising:

digital audio data;

35 sampling frequency data;

a maximum number of quantization bits information; and

40 maximum data transfer rate information;

wherein said digital audio data is sampled at said maximum frequency and quantized in said maximum number of

45 bits with a number of channels of said digital audio data limited by said maximum data transfer rate.

11. A DVD-Audio disk as claimed in claim 10, further comprising compression ratio information of coding of said digital audio data, wherein said number of channels of said digital audio data are also limited by said compression ratio information.

50 12. A DVD-Audio disk as claimed in claim 11, wherein said digital audio data is coded as one of lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding.

13. A DVD-Audio disk as claimed in claim 12, wherein said lossless psychoacoustic coding and pseudo-lossless psychoacoustic coding are performed with a DTS coding system.

55 14. A DVD-Audio disk as claimed in claim 11, wherein said digital audio data is coded as linear pulse code modulated (PCM) coding.

15. A DVD-Audio disk comprising:

a data storage area to store audio data to be reproduced, audio titles each having an audio title set management table followed by a plurality of contiguous audio objects, a plurality of audio stream attributes each having an audio coding mode, a quantization bit number, a sampling frequency and decoding algorithm information relating to a number of audio channels of said audio data, wherein each of said audio objects includes a plurality of audio packs having portions of said audio data corresponding to said decoding algorithm stored in said audio stream attribute.

16. A DVD-Audio disk as claimed in claim 15, wherein each of said audio packs further comprises a padding packet which is increased based upon a number of samples of said audio data.

17. A DVD-Audio disk as claimed in claim 15, wherein a compression rate of said audio data is approximately 2:1 for lossless psychoacoustic coding and approximately 4:1 for pseudo lossless psychoacoustic coding.

18. An apparatus to reproduce data from a DVD, comprising:

a reading unit to read the data from the DVD;

a system controller to determine if an audio title set (AUDIO_TS) of the DVD includes effective data, and controls reproduction of the DVD in a DVD-Audio format if said AUDIO_TS includes said effective data.

19. An apparatus as claimed in claim 18, further comprising:

a data receiver to corrects errors in the read data;

an audio decoder to decode said corrected data;

a digital processor to filter said decoded data; and

an audio output circuit to convert said filtered data to an analog audio signal.

20. An apparatus as claimed in claim 19, wherein said audio decoder comprises:

a stream selector to determine whether said corrected data is linear pulse code modulated (PCM) coded or compression coded;

a linear PCM decoder to decode said linear PCM data to processed data according to a linear PCM decoding method;

a coding data decoder to decode said compression coded data to said processed data according to a corresponding compression decoding method; and

a digital formatter to format said processed data as said decoded data.

21. An apparatus as claimed in claim 18, wherein said system controller controls reproduction of the DVD in a DVD-Video format if said AUDIO_TS does not include said effective data.

22. An apparatus as claimed in claim 21, further comprising:

a data receiver to corrects errors in the read data;

an audio/video decoder to decode said corrected data;

a video output circuit to convert said decoded data to an analog video signal, if said decoded data is indicative of video information and said system controller reproduces the data of the DVD in the DVD-Video format;

a digital processor to filter said decoded data if said decoded data is indicative of audio information, wherein said system controller; and

an audio output circuit to convert said filtered data to an analog audio signal.

23. An apparatus as claimed in claim 22, wherein said audio/video decoder comprises:

- 5 a stream parser to divide said corrected data which is indicative of said video information from said corrected data which is indicative of said audio information;
- a video decoder to decode said corrected data indicative of said video information, to generate said decoded data indicative of said video information; and
- 10 an audio decoder to decode said corrected data indicative of said audio information, to generate said decoded information indicative of said audio information.

24. An apparatus as claimed in claim 22, wherein said audio decoder includes:

- 15 a linear PCM decoder;
- a Dolby AC-3 decoder;
- 20 a coding data decoder; and
- an MPEG decoder;
- 25 wherein said system controller drives the corresponding one of said linear PCM decoder, Dolby AC-3 decoder, coding data decoder, and MPEG decoder, to decode said corrected data indicative of said audio information based upon a coding format of said corrected data indicative of said audio information.

25. A method of reproducing data from a DVD, wherein the DVD has a data zone and an information zone, said information zone storing directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS), wherein said AUDIO_TS includes information on an audio manager (AMG) which stores information on audio titles and said VIDEO_TS includes information on a video manager (VMG) which stores information on video titles, said method comprising the steps of:

- 35 determining whether effective data is stored in said AUDIO_TS, and determining that the disk is a DVD-AUDIO if said effective data is stored in said AUDIO_TS and that the disk is a DVD-Video if said effective data is not stored in said AUDIO_TS;
- locating said AMG by reading said AUDIO_TS if the disk is said DVD-Audio;
- 40 finding a designated one of said audio titles located from said AMG if the disk is said DVD-Audio;
- determining a coding format of said designated audio title and selecting a corresponding decoding format if the disk is said DVD-Audio; and
- 45 reproducing said designated audio title using said determined decoding format if the disk is said DVD-Audio.

26. A method as claimed in claim 25, further comprising the steps of:

- 50 locating said VMG by reading said VIDEO_TS if the disk is said DVD-Video;
- finding a designated one of said video titles located from said VMG if the disk is said DVD-Video; and
- reproducing said designated video title if the disk is said DVD-Video.

55 27. A method as claimed in claim 25 or 26, wherein said step of reproducing said designated audio title comprises the steps of:

- driving an audio decoding circuit to decode audio data of said audio title;

determining operational state of audio decoding circuit;

decoding said audio data using said audio decoding circuit, confirming said operational state of said audio decoding circuit, and outputting said decoded audio data if said operational state is normal; and

stopping the drive of said audio decoding circuit, performing a repair algorithm on said audio data and restarting the drive of said audio decoding circuit, if said operational state is abnormal.

28. A DVD-Audio disk as claimed in Claim 1, wherein if said audio coding mode is linear pulse code modulated (PCM) audio, a maximum number of said audio channels is determined by the following Eq. 1:

$$\text{Eq. 1} \quad N = \frac{Mby}{Fs * Qb},$$

wherein Fs is the sampling frequency(Hz), Qb is the quantization bit number, Mby is the maximum data transfer rate(Mbps) of the DVD-Audio disk, and N is the maximum number of said audio channels determined by the data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

29. A DVD-Audio disk as claimed in Claim 1, wherein if said audio coding mode is a compression coding system, a maximum number of said audio channels is determined by the following Eq. 2:

$$\text{Eq. 2} \quad N = \frac{Mby * Ccy}{Fs * Qb},$$

wherein Fs is the sampling frequency(Hz), Qb is the quantization bit number, Mby is the maximum data transfer rate(Mbps) of the DVD-Audio disk, Ccy is a compression ratio according to a DTS compression coding system and N is the maximum number of said audio channels determined by data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

30. A DVD-Audio disk as claimed in claim 1, wherein if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16bits, 20bits and 24bits, said first to third sampling frequencies are respectively 44.1KHz, 88.2KHz and 176.4KHz, a maximum of said audio channels is 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr}{Fs * Qb},$$

wherein,

Fs is the sampling frequency (Hz) of the data to be reproduced, Qb is the quantization bit number (bits) of the data to be reproduced, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, N is a maximum number of recording channels as determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

31. A DVD-audio disk as claimed in claim 1, wherein if said audio coding mode is pseudo lossless compression coding, said first to third quantization bit numbers of the data to be reproduced before compression are respectively 16 bits, 20 bits and 24 bits, said first to third sampling frequencies are respectively 44.1KHz, 88.2KHz and 176.4KHz, a maximum number of said audio channels 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr * Ccr}{Fs * Qb},$$

wherein,

Fs is the sampling frequency (Hz) of the data to be reproduced, Qb is the quantization bit number (bits) of the data to be reproduced, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, Ccr is a compression ratio according to a DTS compression coding system, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

32. A DVD-Audio disk comprising:

a plurality of audio packs each including

a data zone; and

VIDEO_TS and AUDIO_TS directories positioned at said data zone;

wherein said AUDIO_TS directory includes positional information of an audio manager (AMG), wherein the AMG stores positional information of audio titles of the DVD-Audio disk, and said audio titles include an audio title set information (ATSI) and a plurality of contiguous audio objects (AOBs);

wherein each ATSI includes audio stream attributes having an audio coding mode, first, second or third quantization bits corresponding to the audio data, a first, second, third, fourth, fifth or sixth sampling frequency corresponding to the audio data and decoding algorithm information related to an audio channel number of the audio; and

wherein each AOB includes the audio data corresponding to the decoding algorithm recorded on said audio stream attributes.

33. A DVD-Audio disk as claimed in claim 32, wherein if said audio coding mode is linear pulse code modulated (PCM) audio, said first to third quantization bit numbers are respectively 16 bits, 20 bits and 24 bits, said first to sixth sampling frequencies are respectively 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz and 176.4KHz, a maximum number of said audio channels is 8, and the number of said channels is determined by the following equation:

$$N = \frac{Mbr}{Fs \cdot Qb};$$

wherein,

Fs is the sampling frequency (Hz), Qb is the quantization bit number (bits), Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

34. A DVD-Audio disk as claimed in claim 32, wherein if said audio coding mode is pseudo lossless compression coding, said first to third quantization bit numbers of the audio data before compression are respectively 16 bits, 20 bits and 24 bits, said first to sixth sampling frequencies are respectively 48KHz, 44.1KHz, 96KHz, 88.2KHz, 192KHz and 176.4KHz, a maximum number of said audio channels is 8, and the number of channels is determined by the following equation:

$$N = \frac{Mbr \cdot Ccr}{Fs \cdot Qb};$$

wherein,

Fs is the sampling frequency (Hz) of the audio data, Qb is the quantization bit number (bits) of the audio data, Mbr is a maximum data transfer rate (Mbps) of the DVD-Audio disk, Ccr is a compression ratio according to a DTS compression coding system, and N is a maximum number of recording channels determined by the maximum data transfer rate, sampling frequency and quantization bit number of the DVD-Audio disk.

35. A DVD-Audio disk comprising:

a video directory; and

an audio directory;

wherein both of said video and audio directories contain only audio information.

36. The DVD-Audio disk as claimed in claim 35, wherein the audio information in said video directory has sampling frequencies of at least one of 44.1KHz, 48KHz, 88.2KHz and 96KHz and the audio information in said audio di-

rectory has sampling frequencies of at least one of 44.1KHz, 48KHz, 88.2KHz, 96KHz, 176.4KHz and 192KHz.

36. The DVD-Audio disk as claimed in claim 35, wherein the audio information in said video directory has a sampling frequency of 96KHz, and the audio information in said audio directory has a sampling frequency of 192KHz.

37. The DVD-Audio disk as claimed in claim 35, wherein the audio information in said video directory has a sampling frequency of 88.2KHz, and the audio information in said audio directory has a sampling frequency of 176.4KHz.

38. A DVD-Audio disk comprising:

a video title set directory; and

an audio title set directory to store audio data and control data for allowing reproduction of the audio data.

39. The DVD-Audio disk as claimed in claim 38, wherein the control data comprises a logical data structure containing information on the audio data.

40. The DVD-Audio disk as claimed in claim 38, wherein said video title set directory also stores audio data.

41. The DVD-Audio disk as claimed in claim 38, wherein the second sampling frequency is no greater than a limit of a DVD-Video standard, and the first sampling frequency is above the limit.

42. The DVD-Audio disk as claimed in claim 38, wherein the audio information in said video title set directory has a sampling frequency of at least one of 44.1KHz, 48KHz, 88.2KHz and 96KHz and the audio information in said audio title set directory has a sampling frequency of at least one of 44.1KHz, 48KHz, 88.2KHz, 96KHz, 176.4KHz and 192KHz.

43. The DVD-Audio disk as claimed in claim 38, wherein the audio information in said video title set directory has a sampling frequency of 96KHz, and the audio information in said audio title set directory has a sampling frequency of 192KHz.

44. The DVD-Audio disk as claimed in claim 43, wherein the audio information in said video title set directory has a sampling frequency of 88.2KHz, and the audio information in said audio title set directory has a sampling frequency of 176.4KHz.

45. An apparatus to reproduce data from a DVD, comprising:

a reading unit to read the data from the disk; and

a system controller to determine if an audio directory of the DVD includes audio data and control information of the audio data, and controls reproduction of the audio data from the audio directory if the audio directory includes the audio data and the control information of the audio data.

46. The apparatus as claimed in claim 45, wherein said system controller controls the reproduction of the audio data from the audio directory when the audio data from the audio directory has a sampling frequency of one of 176.4KHz and 192KHz.

47. A method of reproducing data from a DVD, wherein the DVD has a video directory and an audio directory, said method comprising the step of:

determining whether audio data and control information is stored in audio directory determining that the DVD is a DVD-Audio if the audio data and control information is stored in the audio directory and that the DVD is a DVD-Video if the audio data and control information of the audio data is not stored in the audio directory; and

reproducing the audio data from the audio directory according to the control information if the DVD is the DVD-Audio and reproducing the audio data from the audio video directory if the DVD is the DVD-video.

48. The method as claimed in claim 47, wherein said step of reproducing the audio data comprises the steps of:

determining a coding format of the audio data and selecting a corresponding decoding format if the DVD is the DVD-Audio; and reproducing the audio data using said determined decoding format if the DVD is said DVD-Audio.

5 **49.** The method is claimed in claim 47, wherein the audio data from the audio directory of the DVD-Audio has a sampling frequency of one of 176.4KHz and 192KHz, and the audio data from the video directory of the DVD-Video has a sampling frequency of one of 88.2KHz and 96KHz.

10

15

20

25

30

35

40

45

50

55




FIG. 1





FIG. 2



C_IDN#: CELL NUMBER WITHIN A VOB
VOB_IDN#: VOB ID NUMBER WITHIN A VOBS

FIG. 3




FIG. 4




FIG. 5

VIDEO TITLE SET INFORMATION (VTSI)	VIDEO TITLE SET INFORMATION MANAGEMENT TABLE (VTSI_MAT)
VIDEO OBJECT SET FOR VIDEO TITLE SET MENU (VTSM_VOBS)	VIDEO TITLE SET PART OF TITLE SEARCH POINTER TABLE (VTS_PTT_SRPT)
VIDEO OBJECT SET FOR VIDEO TITLE SET TITLE (VTS TT_VOBS)	VIDEO TITLE SET PROGRAM CHAIN INFORMATION TABLE (VTS_PGCIT)
BACKUP OF VIDEO TITLE SET INFORMATION (VTSI_BUP)	VIDEO TITLE SET MENU PGC UNIT TABLE (VTSM_PGCI_UT)
	VIDEO TITLE SET TIME MAP TABLE (VTS_TMPT)
	VIDEO TITLE SET MENU CELL ADDRESS TABLE (VTSM_C_ADT)
	VIDEO TITLE SET MENU VIDEO OBJECT UNIT ADDRESS MAP (VTSM_VOBU_ADMAP)
	VIDEO TITLE SET CELL ADDRESS TABLE (VTS_C_ADT)
	VIDEO TITLE SET VIDEO OBJECT UNIT ADDRESS MAP (VTS_VOBU_ADMAP)

FIG. 6

VTSI_MAT

RBP		CONTENTS	NUMBER OF BYTES
0 TO 11	VTS_ID	VTS IDENTIFIER	12BYTES
12 TO 15	VTS_EA	END ADDRESS OF VTS	4BYTES
16 TO 27	RESERVED	RESERVED	12BYTES
28 TO 31	VTSI_EA	END ADDRESS OF VTSI	4BYTES
32 TO 33	VERN	VERSION NUMBER OF DVD VIDEO SPECIFICATION	2BYTES
34 TO 37	VTS_CAT	VTS CATEGORY	90BYTES
38 TO 127	RESERVED	RESERVED	4BYTES
128 TO 131	VTSI_MAT_EA	END ADDRESS OF VTSI_MAT	60BYTES
132 TO 191	RESERVED	RESERVED	4BYTES
192 TO 195	VTSM_VOBS_SA	START ADDRESS OF VTSM_VOBS	4BYTES
196 TO 199	VTSTT_VOBS_SA	START ADDRESS OF VTSTT_VOBS	4BYTES
200 TO 203	VTS_PTT_SRPT_SA	START ADDRESS OF VTS_PTT_SRPT	4BYTES
204 TO 207	VTS_PGCIT_SA	START ADDRESS OF VTS_PGCIT	4BYTES
208 TO 211	VTSM_PGCI_UT_SA	START ADDRESS OF VTSM_PGCI_UT	4BYTES
212 TO 215	VTS_TMAPT_SA	START ADDRESS OF VTS_TMAPT	4BYTES
216 TO 219	VTSM_C_ADT_SA	START ADDRESS OF VTSM_C_ADT	4BYTES
220 TO 223	VTSM_VOBU_ADMAP_SA	START ADDRESS OF VTSTT_VOBU_ADMAP	4BYTES
224 TO 227	VTS_C_ADT_SA	START ADDRESS OF VTS_C_ADT	4BYTES
228 TO 231	VTS_VOBU_ADMAP_SA	START ADDRESS OF VTS_VOBU_ADMAP	4BYTES
232 TO 255	RESERVED	RESERVED	24BYTES
256 TO 257	VTSM_V_ATR	VIDEO ATTRIBUTE OF VTSM	2BYTES
258 TO 259	VTSM_AST_Ns	NUMBER OF AUDIO STREAMS OF VTSM	2BYTES
260 TO 267	VTSM_AST_ATR	AUDIO STREAM ATTRIBUTE OF VTSM	8BYTES
268 TO 323	RESERVED	RESERVED	56BYTES
324 TO 339	RESERVED	RESERVED	16BYTES
340 TO 341	VTSM_SPST_Ns	NUMBER OF SUB-PICTURE STREAMS OF VTSM	2BYTES
342 TO 347	VTSM_SPST_ATR	SUB-PICTURE STREAMS ATTRIBUTE TABLE OF VTSM	6BYTES
348 TO 511	RESERVED	RESERVED	164BYTES
512 TO 513	VTS_V_ATR	VIDEO ATTRIBUTE OF VTS	2BYTES
514 TO 515	VTS_AST_Ns	NUMBER OF AUDIO STREAMS OF VTS	2BYTES
516 TO 579	VTS_AST_ATRT	AUDIO STREAM ATTRIBUTE TABLE OF VTS	64BYTES
580 TO 595	RESERVED	RESERVED	16BYTES
596 TO 597	VTS_SPST_Ns	NUMBER OF SUB-PICTURE STREAMS OF VTS	2BYTES
598 TO 789	VTS_SPST_ATRT	SUB-PICTURE STREAMS ATTRIBUTE TABLE OF VTS	192BYTES
790 TO 791	RESERVED	RESERVED	2BYTES
792 TO 983	VTS_MU_AST_ATRT	MULTICHANNEL AUDIO STREAMS ATTRIBUTE TABLE OF VTS	192BYTES
984 TO 1023	RESERVED	RESERVED	40BYTES
1024 TO 2047	RESERVED	RESERVED	1024BYTES

FIG. 7

VTS_AST_ATRT

RBP	CONTENTS	NUMBER OF BYTES
516 TO 523	VTS_AST_ATR OF AUDIO STREAM #0	8BYTES
524 TO 531	VTS_AST_ATR OF AUDIO STREAM #1	8BYTES
532 TO 539	VTS_AST_ATR OF AUDIO STREAM #2	8BYTES
540 TO 547	VTS_AST_ATR OF AUDIO STREAM #3	8BYTES
548 TO 555	VTS_AST_ATR OF AUDIO STREAM #4	8BYTES
556 TO 563	VTS_AST_ATR OF AUDIO STREAM #5	8BYTES
564 TO 571	VTS_AST_ATR OF AUDIO STREAM #6	8BYTES
572 TO 579	VTS_AST_ATR OF AUDIO STREAM #7	8BYTES

FIG. 8A

VTS_AST_ATR




FIG. 8B

RBP	CONTENTS	NUMBER OF BYTES
792 TO 815	VTS MU AST ATR OF AUDIO STREAM #0	24BYTES
816 TO 839	VTS MU AST ATR OF AUDIO STREAM #1	24BYTES
840 TO 863	VTS MU AST ATR OF AUDIO STREAM #2	24BYTES
864 TO 887	VTS MU AST ATR OF AUDIO STREAM #3	24BYTES
888 TO 911	VTS MU AST ATR OF AUDIO STREAM #4	24BYTES
912 TO 935	VTS MU AST ATR OF AUDIO STREAM #5	24BYTES
936 TO 959	VTS MU AST ATR OF AUDIO STREAM #6	24BYTES
960 TO 983	VTS MU AST ATR OF AUDIO STREAM #7	24BYTES
	TOTAL	192BYTES

FIG. 9A

VTS_MU_AST_ATR(1)

b191	b190	b189	b188	b187	b186	b185	b184
AUDIO MIXED FLAG		ACH0 MIX MODE		AUDIO CHANNEL CONTENTS			
b183	b182	b181	b180	b179	b178	b177	b176
AUDIO MIXED FLAG		ACH1 MIX MODE		AUDIO CHANNEL CONTENTS			
b175	b174	b173	b172	b171	b170	b169	b168
AUDIO MIXING PHASE		ACH2 MIX MODE		AUDIO CHANNEL CONTENTS			
b167	b166	b165	b164	b163	b162	b161	b160
AUDIO MIXING PHASE		ACH3 MIX MODE		AUDIO CHANNEL CONTENTS			
b159	b158	b157	b156	b155	b154	b153	b152
AUDIO MIXING PHASE		ACH4 MIX MODE		AUDIO CHANNEL CONTENTS			
b151	b150	b149	b148	b147	b146	b145	b144
AUDIO MIXING PHASE		ACH5 MIX MODE		AUDIO CHANNEL CONTENTS			
b143	b142	b141	b140	b139	b138	b137	b136
AUDIO MIXING PHASE		ACH6 MIX MODE		AUDIO CHANNEL CONTENTS			
b135	b134	b133	b132	b131	b130	b129	b128
AUDIO MIXING PHASE		ACH7 MIX MODE		AUDIO CHANNEL CONTENTS			

FIG. 9B




FIG. 9C




FIG. 9D




FIG. 10




FIG. 11




FIG. 12




FIG. 13

AUDIO TITLE SET INFORMATION (ATSI)	AUDIO TITLE SET INFORMATION MANAGEMENT TABLE (ATSI_MAT)
AUDIO OBJECT SET FOR AUDIO TITLE SET MENU (ATSM_AOBS)	AUDIO TITLE SET PART_OF_TITLE SEARCH POINTER TABLE (ATS_PTT_SRPT)
AUDIO OBJECT SET FOR AUDIO TITLE SET TITLE (ATSTT_AOBS)	AUDIO TITLE SET PROGRAM CHAIN INFORMATION TABLE (ATS_PGCIT)
BACKUP OF AUDIO TITLE SET INFORMATION (ATSI_BUP)	AUDIO TITLE SET MENU PGC UNIT TABLE (ATSM_PGCI_UT)
	AUDIO TITLE SET TIME MAP TABLE (ATS_TMPT)
	AUDIO TITLE SET MENU CELL ADDRESS TABLE (ATSM_C_ADT)
	AUDIO TITLE SET MENU AUDIO OBJECT UNIT ADDRESS MAP (ATSM_AOBU_ADMAP)
	AUDIO TITLE SET CELL ADDRESS TABLE (ATS_C_ADT)
	AUDIO TITLE SET AUDIO OBJECT UNIT ADDRESS MAP (ATS_AOBU_ADMAP)

FIG. 14

ATSI_MAT

RBP		CONTENTS	NUMBER OF BYTES
0 TO 11	ATS_ID	ATS IDENTIFIER	12BYTES
12 TO 15	ATS_EA	END ADDRESS OF ATS	4BYTES
16 TO 27	RESERVED	RESERVED	12BYTES
28 TO 31	ATSI_EA	END ADDRESS OF ATSI	4BYTES
32 TO 33	VERN	VERSION NUMBER OF DVD VIDEO SPECIFICATION	2BYTES
34 TO 37	ATS_CAT	ATS CATEGORY	90BYTES
38 TO 127	RESERVED	RESERVED	4BYTES
128 TO 131	ATSI_MAT_EA	END ADDRESS OF ATSI_MAT	60BYTES
132 TO 191	RESERVED	RESERVED	4BYTES
192 TO 195	ATSM_VOBS_SA	START ADDRESS OF ATSM_VOBS	4BYTES
196 TO 199	ATSTT_VOBS_SA	START ADDRESS OF ATSTT_VOBS	4BYTES
200 TO 203	ATS_PTT_SRPT_SA	START ADDRESS OF ATS_PTT_SRPT	4BYTES
204 TO 207	ATS_PGCIT_SA	START ADDRESS OF ATS_PGCIT	4BYTES
208 TO 211	ATSM_PGCIT_UT_SA	START ADDRESS OF ATSM_PGCIT_UT	4BYTES
212 TO 215	ATS_TMAPT_SA	START ADDRESS OF ATS_TMAPT	4BYTES
216 TO 219	ATSM_C_ADT_SA	START ADDRESS OF ATSM_C_ADT	4BYTES
220 TO 223	ATSM_VOBU_ADMAP_SA	START ADDRESS OF ATSTT_VOBU_ADMAP	4BYTES
224 TO 227	ATS_C_ADT_SA	START ADDRESS OF ATS_C_ADT	4BYTES
228 TO 231	ATS_VOBU_ADMAP_SA	START ADDRESS OF ATS_VOBU_ADMAP	4BYTES
232 TO 255	RESERVED	RESERVED	24BYTES
256 TO 257	ATSM_V_ATR	VIDEO ATTRIBUTE OF ATSM	2BYTES
258 TO 259	ATSM_AST_Ns	NUMBER OF AUDIO STREAMS OF ATSM	2BYTES
260 TO 267	ATSM_AST_ATR	AUDIO STREAM ATTRIBUTE OF ATSM	8BYTES
268 TO 323	RESERVED	RESERVED	56BYTES
324 TO 339	RESERVED	RESERVED	16BYTES
340 TO 341	ATSM_SPST_Ns	NUMBER OF SUB-PICTURE STREAMS OF ATSM	2BYTES
342 TO 347	ATSM_SPST_ATR	SUB-PICTURE STREAMS ATTRIBUTE TABLE OF ATSM	6BYTES
348 TO 511	RESERVED	RESERVED	164BYTES
512 TO 513	ATS_V_ATR	VIDEO ATTRIBUTE OF ATS	2BYTES
514 TO 515	ATS_AST_Ns	NUMBER OF AUDIO STREAMS OF ATS	2BYTES
516 TO 579	ATS_AST_ATR	AUDIO STREAM ATTRIBUTE TABLE OF ATS	64BYTES
580 TO 595	RESERVED	RESERVED	16BYTES
596 TO 597	ATS_SPST_Ns	NUMBER OF SUB-PICTURE STREAMS OF ATS	2BYTES
598 TO 789	ATS_SPST_ATRT	SUB-PICTURE STREAMS ATTRIBUTE TABLE OF ATS	192BYTES
790 TO 791	RESERVED	RESERVED	2BYTES
792 TO 1298	ATS_MU_AST_ATRT	MULTICHANNEL AUDIO STREAMS ATTRIBUTE TABLE OF ATS	507BYTES
1299 TO 1299	RESERVED	RESERVED	749BYTES

FIG. 15




FIG. 16

ATS_AST_ATRT

RBP	CONTENTS	NUMBER OF BYTES
516 TO 523	ATS_AST_ATR OF AUDIO STREAM #0	8BYTES
524 TO 531	ATS_AST_ATR OF AUDIO STREAM #1	8BYTES
532 TO 539	ATS_AST_ATR OF AUDIO STREAM #2	8BYTES
540 TO 547	ATS_AST_ATR OF AUDIO STREAM #3	8BYTES
548 TO 555	ATS_AST_ATR OF AUDIO STREAM #4	8BYTES
556 TO 563	ATS_AST_ATR OF AUDIO STREAM #5	8BYTES
564 TO 571	ATS_AST_ATR OF AUDIO STREAM #6	8BYTES
572 TO 579	ATS_AST_ATR OF AUDIO STREAM #7	8BYTES

FIG. 17A

ATS_AST_ATR




FIG. 17B

RBP	CONTENTS	NUMBER OF BYTES
792 TO 830	ATS_MU_AST_ATR OF AUDIO STREAM #0	39BYTES
831 TO 869	ATS_MU_AST_ATR OF AUDIO STREAM #1	39BYTES
870 TO 908	ATS_MU_AST_ATR OF AUDIO STREAM #2	39BYTES
909 TO 947	ATS_MU_AST_ATR OF AUDIO STREAM #3	39BYTES
948 TO 986	ATS_MU_AST_ATR OF AUDIO STREAM #4	39BYTES
987 TO 1025	ATS_MU_AST_ATR OF AUDIO STREAM #5	39BYTES
1026 TO 1064	ATS_MU_AST_ATR OF AUDIO STREAM #6	39BYTES
1065 TO 1103	ATS_MU_AST_ATR OF AUDIO STREAM #7	39BYTES
1104 TO 1142	ATS_MU_AST_ATR OF AUDIO STREAM #8	39BYTES
1143 TO 1181	ATS_MU_AST_ATR OF AUDIO STREAM #9	39BYTES
1182 TO 1220	ATS_MU_AST_ATR OF AUDIO STREAM #10	39BYTES
1221 TO 1259	ATS_MU_AST_ATR OF AUDIO STREAM #11	39BYTES
1260 TO 1298	ATS_MU_AST_ATR OF AUDIO STREAM #12	39BYTES
	TOTAL	507BYTES

FIG. 18A

ATS_MU_AST_ATR_EXT(1)




FIG. 18B




FIG. 18C




FIG. 19




FIG. 20




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 22




FIG. 23




FIG. 24A




FIG. 24B




FIG. 24C




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 867 877 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
22.09.1999 Bulletin 1999/38

(51) Int Cl.⁶: **G11B 20/12**, **G11B 27/28**,
G11B 20/10

(43) Date of publication A2:
30.09.1998 Bulletin 1998/40

(21) Application number: **98302261.7**

(22) Date of filing: **25.03.1998**

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: **Samsung Electronics Co., Ltd.**
Suwon-city, Kyungki-do (KR)

(72) Inventor: **Heo, Jung-Kwon**
Songpa-gu, Seoul (KR)

(30) Priority: **25.03.1997 KR 9710330**
09.10.1997 KR 9751861

(74) Representative: **Chugg, David John**
Appleyard Lees,
15 Clare Road
Halifax, West Yorkshire HX1 2HY (GB)

(54) **DVD-audio disk, and apparatus and method for playing the same**

(57) A DVD-Audio which includes a data zone for storing data to be reproduced and an information zone for storing information on the data to be reproduced. The information zone includes directories of a video title set (VIDEO_TS) and an audio title set (AUDIO_TS). The AUDIO_TS directory includes information on an audio manager (AMG) having information on audio titles. The data zone includes the audio titles each having an audio title set information (ATSI) followed by a plurality of contiguous audio objects (AOBs). The ATSI includes a plurality of audio stream attributes each having an audio coding mode, first to third quantization bit numbers, first to third sampling frequencies and decoding algorithm information relating to the number of audio channels. Each of the AOBs includes a plurality of audio packs recorded with audio data corresponding to the decoding algorithm stored in the audio stream attribute.




FIG. 1

EP 0 867 877 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 2261

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	EP 0 737 008 A (TOKYO SHIBAURA ELECTRIC CO) 9 October 1996 (1996-10-09) * figures 1,23,43,46,49 * * column 11, line 24 - line 39 * * column 11, line 58 - column 12, line 5 * * column 22, line 48 - column 24, line 39 * * * column 30, line 17 - line 23 * * column 40, line 18 - column 41, line 47 *	15	G11B20/12 G11B27/28 G11B20/10
Y		35	
A		5-11,14,16,18-20,22-24,32,35,39,40,46,48	
X	EP 0 714 098 A (TOKYO SHIBAURA ELECTRIC CO) 29 May 1996 (1996-05-29) * figures 4,18 * * column 9, line 8 - line 18 * * column 13, line 27 - line 29 * * column 14, line 55 - column 15, line 10 * * * column 17, line 6 - line 16 *	39-41	TECHNICAL FIELDS SEARCHED (Int.Cl.8) G11B
Y		35	
A		1,4,5,7,9,18,25,32,46,48	
E,L	EP 0 855 715 A (SAMSUNG ELECTRONICS CO LTD) 29 July 1998 (1998-07-29) * the whole document *	10-17,46	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 July 1999	Examiner Ogor, M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P0401)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 2261

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
E	EP 0 892 404 A (VICTOR COMPANY OF JAPAN) 20 January 1999 (1999-01-20) * figures 2,12,20,26,28,30,32,33,40 * * column 10, line 14 - line 27 * * column 11, line 52 - column 13, line 22 * * column 21, line 55 - column 23, line 7 * * column 23, line 27 - column 26, line 17 * * column 39, line 36 - line 48 *	1,9-15, 28,29, 32,39-42	
P,A	STOLZMANN J: "DVD: GRUNDLAGEN, TECHNISCHE BETRACHTUNG" FERNSEH UND KINOTECHNIK, vol. 51, no. 11, 1 November 1997 (1997-11-01), pages 716-718, 720, 72, XP000765318 ISSN: 0015-0142 * page 720 * * page 722 - page 724 *	1,4,5,9, 10,14, 18,25, 32,35, 46,48	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 July 1999	Examiner Ogor, M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 2261

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0737008 A	09-10-1996	JP 8336104 A	17-12-1996
		US 5745643 A	28-04-1998
EP 0714098 A	29-05-1996	JP 8147939 A	07-06-1996
		AT 175804 T	15-01-1999
		AU 693282 B	25-06-1998
		AU 3935995 A	17-06-1996
		BR 9506563 A	28-10-1997
		CA 2181265 A	30-05-1996
		CN 1139493 A	01-01-1997
		DE 69507270 D	25-02-1999
		EP 0869497 A	07-10-1998
		WO 9616410 A	30-05-1996
		NO 963071 A	06-09-1996
		US 5778142 A	07-07-1998
		JP 10083661 A	31-03-1998
		JP 2747262 B	06-05-1998
		JP 8263969 A	11-10-1996
EP 0855715 A	29-07-1998	JP 10208403 A	07-08-1998
EP 0892404 A	20-01-1999	JP 11039798 A	12-02-1999
		JP 11086455 A	30-03-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82